

FFB. pp 26

gucose ↑ 5/16 6/87
135

criteria for a recommended standard....

OCCUPATIONAL EXPOSURE TO METHYL ALCOHOL

June 86

Unilateral blindness 31

Blindness - OAR-515



U.S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE
Public Health Service
Center for Disease Control
National Institute for Occupational Safety and Health

MARCH 1976

For sale by the Superintendent of Documents, U.S. Government
Printing Office, Washington, D.C. 20402

FILE COPY

pp 43

same as ppm

Grain Alcohol 1 mg/liter = 1 ppm.

pp 68 Symptoms

6 ml → death pp 49

Characteristic Symptoms - 70
Ingestion Variations - 71

PREFACE

The Occupational Safety and Health Act of 1970 emphasizes the need for standards to protect the health and safety of workers exposed to an ever-increasing number of potential hazards at their workplace. The National Institute for Occupational Safety and Health has projected a formal system of research, with priorities determined on the basis of specified indices, to provide relevant data from which valid criteria for effective standards can be derived. Recommended standards for occupational exposure, which are the result of this work, are based on the health effects of exposure. The Secretary of Labor will weigh these recommendations along with other considerations such as feasibility and means of implementation in developing regulatory standards.

It is intended to present successive reports as research and epidemiologic studies are completed and as sampling and analytical methods are developed. Criteria and standards will be reviewed periodically to ensure continuing protection of the worker.

I am pleased to acknowledge the contributions to this report on methyl alcohol by members of my staff and the valuable constructive comments by the Review Consultants on Methyl Alcohol, by the ad hoc committees of the American Industrial Hygiene Association and the American Medical Association, and by Robert B. O'Connor, M.D., NIOSH consultant in occupational medicine. The NIOSH recommendations for standards are not

necessarily a consensus of all the consultants and professional societies that reviewed this criteria document on methyl alcohol. Lists of the NIOSH Review Committee members and of the Review Consultants appear on the following pages.



John F. Finklea, M.D.

Director, National Institute for
Occupational Safety and Health

The Division of Criteria Documentation and Standard Development, National Institute for Occupational Safety and Health, had primary responsibility for development of the criteria and the recommended standard for methyl alcohol. Stanford Research Institute developed the basic information and the final document for consideration by NIOSH staff and consultants under contract No. CDC-99-74-31. Gamil Debbas, Ph.D., was the NIOSH criteria manager during the development of this document.

REVIEW COMMITTEE
NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH

John F. Bester, Ph.D.
Office of Extramural Coordination
and Special Projects

George J. Butler
Western Area Occupational Health Laboratory

Ardith A. Grote
Division of Physical Sciences and Engineering

William H. Perry
Division of Training and Manpower Development

Harry B. Plotnick, Ph.D.
Division of Biomedical and Behavioral Science

James H. Price
Division of Technical Service

Theodore W. Tholburn, M.D.
Division of Surveillance, Hazard Evaluation
and Field Studies

NIOSH REVIEW CONSULTANTS ON METHYL ALCOHOL

Jack R. Cooper, Ph.D.
Professor of Pharmacology
Yale University
School of Medicine
New Haven, Connecticut 06510

John C. Lumsden,
Chief, Occupational Health Branch
Department of Human Resources
Division of Health Services
Raleigh, North Carolina 27602

Anthony Mazzocchi
Director Citizenship - Legislative Department
Oil, Chemical and Atomic International Workers Union
Washington, DC 20036

Arthur J. Paik, Ph.D.
Assistant Vice-President
Hoffmann-LaRoche, Inc.
Nutley, New Jersey 07110

George Roush, Jr., M.D.
Monsanto Company
St. Louis, Missouri 63166

Edward B. Truitt, Jr., Ph.D.
Department of Pharmacology
George Washington University
School of Medicine
Washington, DC 20037

CRITERIA DOCUMENT:
RECOMMENDATIONS FOR AN OCCUPATIONAL
EXPOSURE STANDARD FOR METHYL ALCOHOL

Table of Contents

	<u>Page</u>
PREFACE	iii
REVIEW COMMITTEES	vi
I. RECOMMENDATIONS FOR A METHYL ALCOHOL STANDARD	
Section 1 - Environmental (Workplace Air)	2
Section 2 - Medical	2
Section 3 - Labeling (Posting)	3
Section 4 - Personal Protective Equipment and Clothing	5
Section 5 - Informing Employees of Hazards from Methyl Alcohol	9
Section 6 - Work Practices	10
Section 7 - Sanitation Practices	15
Section 8 - Monitoring and Recordkeeping	15
II. INTRODUCTION	17
III. BIOLOGIC EFFECTS OF EXPOSURE	
Extent of Exposure	19
Historical Reports	20
Effects on Humans	24
Epidemiologic Studies	45
Animal Toxicity	53
Correlation of Exposure and Effect	68
IV. ENVIRONMENTAL DATA AND ENGINEERING CONTROLS	
Sampling and Analysis	76
Environmental Levels	78
Control of Exposure	81
V. DEVELOPMENT OF STANDARD	
Basis for Previous Standards	83
Basis for the Recommended Environmental Standard	85
VI. WORK PRACTICES	91
VII. REFERENCES	95
VIII. APPENDIX I - Method For Sampling Methyl Alcohol In Air	102
IX. APPENDIX II - Analytical Method for Methyl Alcohol	108

Table of Contents (Continued)

	<u>Page</u>
X. APPENDIX III - Material Safety Data Sheet	115
XI. APPENDIX IV - Combustible Gas Meter	125
XII. APPENDIX V - Future Research Priorities for Methyl Alcohol	126
XIII. TABLES AND FIGURE	129

I. RECOMMENDATIONS FOR A METHYL ALCOHOL STANDARD

The National Institute for Occupational Safety and Health (NIOSH) recommends that employee exposure to methyl alcohol in the workplace be controlled by adherence to the following sections. The standard is designed to protect the health and safety of workers for up to a 10-hour workday, 40-hour workweek, over a working lifetime. Compliance with all sections of the standard should therefore prevent adverse effects of methyl alcohol on the health and safety of employees. The recommended standard is measurable by techniques that are valid, reproducible, and available to industry and governmental agencies. Sufficient technology exists to permit compliance with the recommended standard. Although the workplace environmental limits are considered to be safe levels based on current information, they should be regarded as the upper boundary of exposure and every effort should be made to maintain the exposure as low as is technically feasible. The criteria and standard will be subject to review and revision as necessary.

These criteria and the recommended standard apply to occupational exposure of workers to the aliphatic alcohol CH_3OH , hereinafter referred to as "methyl alcohol." Synonyms for methyl alcohol include wood spirit, carbinol, wood alcohol, wood naphtha, Columbian spirit, colonial spirit, methylol, pyroxylic spirit, monohydroxymethane, methyl hydroxide, and methanol. "Action level" means half of the time-weighted average (TWA) environmental exposure limit for methyl alcohol. "Occupational exposure to methyl alcohol" means exposure at or above the action level. If "exposure" to other chemicals also occurs, for example to a combination of methyl

alcohol and acetone, provisions of any applicable standard for the other chemicals shall also be followed.

Section 1 - Environmental (Workplace Air)

(a) Concentration

Occupational exposure to methyl alcohol shall be controlled so as not to exceed 200 parts per million (200 ppm) parts of air by volume (262 milligrams per cubic meter of air) determined as a time-weighted average (TWA) exposure for up to a 10-hour workday, 40-hour workweek, with a ceiling of 800 ppm (1,048 mg/cu m) as determined by a sampling time of 15 minutes.

(b) Sampling, Calibration, and Analysis

Procedures for collection and analysis of environmental samples shall be as provided in Appendices I and II, or by any methods shown to be equivalent in precision, sensitivity, and accuracy to the methods specified.

Section 2 - Medical

Medical surveillance shall be made available as specified below for all employees occupationally exposed to methyl alcohol.

(a) Preplacement medical examinations shall include:

(1) A comprehensive work history.

(2) A complete physical examination which should include an ophthalmologic examination.

(b) Medical surveillance and management including ophthalmologic examination shall be promptly provided to any employee who develops ocular symptoms, or has had methyl alcohol splashed in the eyes, or has ingested methyl alcohol, or has been accidentally overexposed by inhalation or dermal contact.

(c) Periodic medical surveillance should be performed annually for all employees occupationally exposed to methyl alcohol.

(d) Initial examinations for employees who are occupationally exposed to methyl alcohol at the time of the promulgation of a standard incorporating these recommendations shall be made available within 6 months.

(e) Medical records shall be maintained for all persons with occupational exposure to methyl alcohol and for maintenance personnel with occasional exposure. Pertinent medical records, including information on required medical examinations, shall be retained for at least 5 years after the termination of the individual's employment.

(f) Pertinent records shall be available to the designated medical representatives of the Secretary of Health, Education, and Welfare, of the Secretary of Labor, of the employee or former employee, and of the employer.

Section 3 - Labeling (Posting)

(a) Labeling

The following warning sign shall be affixed in a readily visible location on methyl alcohol storage tanks or containers:

METHYL ALCOHOL
(METHANOL)

WARNING! FLAMMABLE

CAN BE FATAL OR CAUSE BLINDNESS IF SWALLOWED

Keep away from heat, sparks, and open flame.
No smoking permitted.
Do not take internally.
Keep container closed.
Avoid prolonged or repeated breathing of vapor
or contact with skin.
Avoid contact with eyes.
Use with adequate ventilation.

First Aid: In case of eye or skin contact, flush thoroughly with copious amounts of water. In case of accidental swallowing, call a physician and induce vomiting if the patient is conscious. Change clothing if contaminated.

In case of

Fire: Use water, spray, "alcohol" type foam, dry chemical, or carbon dioxide extinguishers.

Spill: Flush area with water spray.

(b) Posting

Areas in which methyl alcohol is present shall be posted with a sign reading:

METHYL ALCOHOL
(Methanol)

WARNING! FLAMMABLE

HARMFUL IF INHALED
CAN BE FATAL OR CAUSE BLINDNESS IF SWALLOWED
IRRITATING TO SKIN OR EYES

No smoking permitted.
Provide adequate ventilation.

These warning signs shall be printed both in English and in the predominant language of non-English-speaking employees. All employees shall be trained and informed of the hazardous areas with special instructions given to illiterate employees.

Section 4 - Personal Protective Equipment and Clothing

(a) Protective Clothing

(1) Appropriate protective clothing, including gloves, aprons, suits, boots, and face shields that are impervious to methyl alcohol, shall be provided and worn where needed to prevent repeated or prolonged skin contact.

(2) Soap and water shall be made available to cleanse contaminated skin.

(3) Unless clothing impervious to methyl alcohol is being worn, a change of clothing shall be made immediately available to and used by each employee whose clothes become contaminated with liquid methyl alcohol.

(b) Eye Protection

Chemical safety goggles or face shields meeting the requirements of 29 CFR 1910.133 and ANSI Z87.1-1968 shall be provided and worn in any operation in which there is a reasonable probability that methyl alcohol may be splashed into the eyes.

(c) Respiratory Protection

(1) Engineering controls shall be used wherever feasible to maintain methyl alcohol concentrations below the TWA and ceiling environmental limits. Such control equipment shall be sparkproof.

Compliance with the environmental limits may not be achieved by the use of respirators except:

(A) During the time period necessary to install or test the required engineering controls.

(B) For nonroutine operations such as brief exposures at concentrations in excess of the environmental limits resulting from maintenance or repair activities.

(C) During emergencies when air concentrations of methyl alcohol may exceed the environmental limits.

(2) When a respirator is permitted by paragraph (c)(1) of this Section, it shall be selected and used pursuant to the following requirements:

(A) For the purpose of determining the type of respirator to be used, the employer shall measure the atmospheric concentration of methyl alcohol in the workplace initially and thereafter whenever process, worksite, climate, or control changes occur which are likely to increase the methyl alcohol concentrations. This requirement shall not apply when only atmosphere-supplying positive pressure respirators will be used. The employer shall ensure that no employee is being exposed to methyl alcohol in excess of the environmental limits because of improper respirator selection, fit, use, or maintenance.

(B) A respiratory protection program meeting the requirements of 29 CFR 1910.134 as amended shall be established and enforced by the employer,

(C) The employer shall provide respirators in accordance with Table I-1 and shall ensure that the employee uses the

respirator provided.

(D) Respiratory protective devices described in Table I-1 shall be those approved under the provisions of 30 CFR 11.

(E) Respirators specified for use in higher concentrations of methyl alcohol may be used in atmospheres of lower concentrations.

(F) The employer shall ensure that respirators are adequately cleaned, and that employees are instructed on the use of respirators assigned to them and on how to test for leakage.

(G) Where an emergency may develop which could result in employee overexposure to methyl alcohol, the employer shall provide respiratory protection as listed in Table I-1.

TABLE I-1

RESPIRATOR SELECTION GUIDE FOR PROTECTION AGAINST METHYL ALCOHOL

Concentration	Respirator Type
Less than or equal to 2,000 ppm	(1) A supplied-air respirator (2) A self-contained breathing apparatus
Less than or equal to 10,000 ppm	(1) A supplied-air respirator with a full facepiece, helmet, or hood (2) Any self-contained breathing apparatus with a full facepiece
Less than or equal to 25,000 ppm	A Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure mode or with a full facepiece, helmet, or hood operated in continuous-flow mode
Greater than 25,000 ppm CAUTION! The lower explosive limit is approximately 67,000 ppm	(1) Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode (2) A combination respirator which includes a Type C supplied-air respirator with a full facepiece operated in pressure-demand or other positive pressure or continuous-flow mode and an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive pressure mode
Firefighting	Self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode
Escape	(1) Any gas mask providing protection against methyl alcohol (2) Any escape self-contained breathing apparatus

Section 5 - Informing Employees of Hazards from Methyl Alcohol

(a) Each employee occupationally exposed to methyl alcohol shall be informed of the hazards, especially flammability; the consequences of overexposure by ingestion, inhalation, and skin contact; appropriate emergency procedures; proper conditions for safe use, and precautions to minimize exposure. Records of such training should be kept to facilitate checking of the training and frequency of such training for each worker. The employee should be reformed at least once a year, or whenever there is a process change. This appraisal shall include, as a minimum, all information set forth in Appendix III which is applicable to that specific product or material containing methyl alcohol.

(b) Information as required shall be recorded on the US Department of Labor form OSHA-20, "Material Safety Data Sheet" shown in Appendix III, or on a similar form approved by the Occupational Safety and Health Administration, US Department of Labor.

(c) Each employee shall be informed of the location of the information described in paragraph (b) of this Section. This information shall be kept on file at each establishment or department and shall be readily accessible to all employees occupationally exposed to methyl alcohol.

Section 6 - Work Practices

(a) Emergency Procedures

For all work areas in which there is potential for emergencies, procedures as specified below, as well as any other procedures appropriate for a specific operation or process, shall be formulated in advance and employees shall be instructed in their implementation.

(1) Procedures shall include prearranged plans for obtaining emergency medical care and for necessary transportation of injured workers.

(2) Firefighting procedures shall be established and implemented. These shall include procedures for emergencies involving the release of methyl alcohol vapor. In case of fire, methyl alcohol sources shall be shut off or removed. Containers shall be removed or cooled with water spray. Chemical foam, carbon dioxide, or dry chemicals should be used for fighting methyl alcohol fires, and proper respiratory protection and protective clothing shall be worn.

(3) Approved eye, skin, and respiratory protection as specified in Section 4 shall be used by personnel essential to emergency operations.

(4) Nonessential employees shall be evacuated from exposure areas during emergencies. Perimeters of hazardous exposure areas shall be delineated, posted, and secured.

(5) Personnel properly trained in the procedures and adequately protected against the attendant hazards shall shut off sources of methyl alcohol, clean up spills, and immediately repair leaks.

(b) Exhaust Systems

Engineering procedures shall be established to reduce exposure of employees to methyl alcohol through implementation of adequate ventilation methods. When a local exhaust ventilation system is used, it shall be designed and maintained to prevent the accumulation or recirculation of methyl alcohol vapor into the workroom, so that the airborne methyl alcohol concentrations do not exceed the environmental limits. Exhaust systems discharging into outside air must conform with applicable local, state, and federal air pollution regulations. When mechanical ventilation is used to control exposure, measurements which demonstrate system efficiency (eg, air velocity, static pressure, or air volume) shall be made at least every 3 months. Measurements of system efficiency shall also be made within 5 workdays of any change in production, process, or control that might result in an increase in airborne concentrations. When a fan is located in duct work and where methyl alcohol is likely to be present at concentrations at or above 0.67% (one-tenth the lower flammable limit, 67,000 ppm), the fan rotating element shall be of nonsparking material or the casting shall be coated with, or consist of, a nonsparking material. The ventilation system shall contain devices along the length of the exhaust system intended to prevent the propagation of flashbacks.

(c) Loading and Unloading

The handling and storage of methyl alcohol shall comply with NFPA Article 30 for flammable and combustible liquids.

(1) Safety showers and eyewash fountains shall be installed in loading and unloading areas.

(2) Fire extinguishers approved for Class I B fires, such as dry chemical extinguishers, shall be available in loading and unloading areas. Fire extinguishers shall be inspected annually and recharged or replaced if necessary.

(3) The equipment required by c(1) of this Section shall be inspected regularly to ensure that it is in working order. The employer shall ensure that such inspection is performed by a qualified person.

(4) In the event of a leak that may lead to airborne concentrations exceeding the environmental limits, the operations shall be stopped and resumed only after necessary repair or replacement has been completed.

(5) Bonding facilities for protection against static sparks during the loading of tank vehicles shall be provided as required in 29 CFR 1910.106(f)(3)(IV).

(d) Methyl Alcohol Car and Truck Loading Procedure

(1) Smoking, matches, or lighters shall be prohibited in the methyl alcohol car and truck loading area.

(2) The safety shower and eyewash fountain in the loading and unloading area shall be checked regularly.

(3) A wheel chock, a car loading sign, and the derail shall be placed in position and ground cables attached before connecting any lines to the tank car.

(4) Wheel chocks, ground cables, and loading sign shall be in place before connecting any lines to a trailer.

(5) Ground cables shall be removed only when loading or unloading lines have been removed and the dome covers have been secured.

(6) Rubber gloves and face shields shall be used where the possibility of methyl alcohol splashes exists. Breathing of methyl alcohol vapor should be avoided whenever possible.

(7) Any part of the body on which methyl alcohol has been spilled should be washed immediately with large quantities of water. Eyes should be flushed immediately with copious amounts of water and the incident should be reported immediately to the appropriate health unit.

(e) Storage

Storage of bulk amounts shall meet the requirements for Class I B flammable liquid storage as specified in 29 CFR 1910.106(b).

(f) Disposal

Spills of large amounts of methyl alcohol should be washed with water. Discarding of waste shall be in compliance with applicable EPA standards. When it is not possible to wash a spill with water, the area should be cordoned off until cleanup operations have been completed. If a vacuum truck is used to remove the alcohol, care must be taken to ensure that there are no sources of ignition and that sufficient flashback devices are provided.

(g) Vessel Entry

Vessels include tanks and reactors in which occupational exposure to airborne methyl alcohol may exist. Special work procedures are required for entering vessels. Before allowing an employee to enter the vessel, a technically competent person authorized by the employer shall sign a safety permit declaring the job to be safe. The following precautions shall be taken to ensure safety:

(1) All lines shall be disconnected or blocked while the vessel is being cleaned. All valves or pumps leading to and from the vessel shall be locked out or tagged out.

(2) The vessel shall be washed with water and purged with air, or with nitrogen and then with air.

(3) A calibrated combustible gas meter shall be used to check for explosion hazard. The test should be performed by a person trained in the use of the combustible gas meter. (See Appendix IV)

(4) The vessel shall then be checked for airborne methyl alcohol, oxygen, and other likely contaminant concentrations and safe levels of each assured, unless a positive pressure respirator is used.

(5) If a respirator is necessary, an appropriate type shall be provided to the employee. Section 4(c) of this chapter describes the types of respirators which are suitable under various conditions.

(6) Each employee shall use a lifeline when entering a vessel. At least 2 other persons equipped with respiratory protection shall watch at all times from the outside. At least one other person shall be available to assist in emergencies.

(h) General Housekeeping

Employers shall ensure that proper maintenance of equipment is provided in order to minimize the accidental escape of methyl alcohol. Cleanup of spills and repair of equipment and leaks shall be performed as soon as practical.

Section 7 - Sanitation Practices

(a) Food Facilities

In accordance with the provisions of 29 CFR 1910.141(g)(2) and (g)(4), the consumption or storage of food or beverages shall be prohibited in the worksite.

(b) Smoking

Smoking shall be prohibited in areas where methyl alcohol is used, transferred, stored, or manufactured.

(c) Handwashing Facilities

Adequate facilities providing soap and water for handwashing shall be made available.

Section 8 - Monitoring and Recordkeeping

Workroom areas where it has been determined on the basis of an industrial hygiene survey that environmental levels are below half the time-weighted average environmental limit are not considered to have occupational exposure to methyl alcohol. Records of these surveys, including the basis for concluding that environmental concentrations are below the action level, shall be maintained until a new survey is completed. Surveys shall be repeated when a process change indicates to a qualified person in authority the need for reevaluation.

Requirements set forth below apply to work areas in which there is occupational exposure to methyl alcohol.

(a) An adequate number of breathing zone samples shall be collected and analyzed to characterize the TWA and ceiling concentrations of each operation and work location in which there is occupational exposure

to methyl alcohol.

This sampling and analysis shall be repeated every 6 months except as otherwise indicated by a professional industrial hygienist. The first sampling period shall be completed within 6 months of the effective date of the promulgation of a standard based on these recommendations. Additional sampling and analysis shall be performed whenever changes in process, worksite, climate, or engineering control are likely to cause an increase in airborne concentrations. If initial, periodic, or special evaluations indicate TWA or ceiling concentration limits are exceeded, corrective engineering or other control measures shall be promptly instituted to ensure the safety of employees, until concentrations below these environmental limits are achieved. In such cases, sampling of each operation and work location shall be conducted at least monthly until two consecutive 30-day sampling periods have shown that concentrations of methyl alcohol are at or below the workplace environmental limits.

(b) Records shall be maintained and shall include sampling and analytical methods, types of respiratory protection used, and TWA and ceiling concentrations found. Each employee shall have access to data on his own environmental exposures. Pertinent records of required medical examinations, including records of occupational accidents and environmental exposures within the workplace, shall be maintained for 5 years after the worker's employment has ended, and shall be available to the designated medical representatives of the Secretary of Labor, of the Secretary of Health, Education, and Welfare, of the employer, and of the employee or former employee.

II. INTRODUCTION

This report presents the criteria and the recommended standard based thereon which were prepared to meet the need for preventing occupational diseases arising from exposure to methyl alcohol. The criteria document fulfills the responsibility of the Secretary of Health, Education, and Welfare, under Section 20(a)(3) of the Occupational Safety and Health Act of 1970 to "...develop criteria dealing with toxic materials and harmful physical agents and substances which will describe...exposure levels at which no employee will suffer impaired health or functional capacities or diminished life expectancy as a result of his work experience."

The National Institute for Occupational Safety and Health (NIOSH), after a review of data and consultation with others, formalized a system for the development of criteria upon which standards can be established to protect the health of employees from exposure to hazardous chemical and physical agents. It should be pointed out that any criteria and recommended standard should enable management and labor to develop better engineering controls resulting in more healthful work practices and should not be used as a final goal.

These criteria for a standard for methyl alcohol are in a continuing series of criteria developed by NIOSH. The recommended standard applies only to the processing, manufacture, and use of methyl alcohol in products as applicable under the Occupational Safety and Health Act of 1970. The standard was not designed for the population-at-large, and any extrapolation beyond occupational exposures is not warranted. It is intended to (1) protect against development of acute and chronic methyl

alcohol poisoning, (2) be measurable by techniques that are valid, reproducible, and available to industry and official agencies, and (3) be attainable with existing technology.

Areas in which research is needed are epidemiologic studies on humans, primate studies to help develop a dose-response relationship and understand the mechanism of toxicity for methyl alcohol and its metabolites. Additional studies are needed to investigate the possibility of mutagenic, teratogenic, or carcinogenic effects of methyl alcohol. Further work is needed to develop improved sampling and analytical procedures for this substance.

III. BIOLOGIC EFFECTS OF EXPOSURE

Extent of Exposure

Methyl alcohol, CH₃OH, also called methanol, is the first member of a homologous series of monohydric aliphatic alcohols. At room temperature, methyl alcohol is a colorless, neutral liquid possessing a mild distinctive odor. [1] Additional chemical and physical properties of methyl alcohol are presented in Table XIII-1. [2,3,4]

The greater part of methyl alcohol manufactured in the US is produced synthetically. [5] One widely used synthetic process is the "medium pressure process" which involves the reduction of carbon monoxide (containing small amounts of carbon dioxide) with hydrogen. The reduction step is carried out at 250-400 C and at 100-600 atmospheres pressure using a catalyst. [1]

During the years 1968-73, synthetic methyl alcohol production in the US increased at an average annual rate of over 13.2%. In 1973, the production of synthetic methyl alcohol amounted to slightly over seven billion pounds, around one billion gallons. In addition, an estimated 10 million pounds (1.5 million gallons) of "natural" (eg, from wood distillation) methyl alcohol were produced. [5]

Methyl alcohol is used in a variety of industrial processes. The major use is in the production of formaldehyde which amounted to 39% of the methyl alcohol consumed in the US in 1973. [5] Other commercial uses of methyl alcohol are in the production of chemical derivatives, such as dimethyl terephthalate, methyl halides, methyl methacrylate, acetic acid, and methylamines, and because of its solvent properties, methyl alcohol is

also used in paints, varnishes, cements, and other formulations such as inks and dyes. [1,5] Table XIII-2 lists the consumption of methyl alcohol by product and quantity produced in the US for the year 1973. [5]

A number of occupations with potential exposure to methyl alcohol are listed in Table XIII-3. [6]

NIOSH estimates that approximately 175,000 workers in the US are potentially exposed to methyl alcohol.

Historical Reports

Taylor [7] first identified methyl alcohol in 1812 when he isolated it from the pyroligneous acid which resulted from the destructive distillation of wood. Because of its reaction with sulfuric acid, he incorrectly classified it as an ether and named it "pyroligneous aether." Dumas and Peligot [8] isolated methyl alcohol (wood alcohol) in a similar fashion and correctly identified it as an alcohol. In addition, they studied some of the chemical and physical properties of wood alcohol.

In 1855, MacFarlan [9] reported on the industrial utility of "methylated spirit" as a substitute for the higher priced, strictly regulated "spirit of wine" (ethyl alcohol). Methylated spirit was a mixture of "wood naphtha" (methyl alcohol) and "spirit of wine" (ethyl alcohol) usually in a proportion of 1 to 9, respectively. MacFarlan also noted the toxic hazard associated with the industrial use of pure methyl alcohol, "as opposed to methylated spirit," indicating that the former affected the eyes of workers while the vapor of the latter rarely did. This constitutes one of the earliest references to the occupational hazard

of methyl alcohol found in the literature.

Wood in 1906 [10] stated that since the wood alcohol in commercial use prior to 1896 was a vile-smelling, "nauseous-tasting" liquid, there was little possibility of its being voluntarily ingested and he reported that cases of methyl alcohol poisoning by ingestion were rare prior to the turn of the century. Around 1896, commercial preparations in which the wood alcohol was deodorized and purified began to appear on the market. [10] Along with this development and an increase in production and use, there was also a dramatic increase in the number of reported cases of serious systemic poisoning resulting from the ingestion, inhalation, or percutaneous absorption of methyl alcohol. By 1904, Wood and Buller [11] were able to compile a collection of case histories of methyl alcohol poisoning. This collection included 54 previously published cases of blindness or blindness followed by death attributed to the drinking or the inhalation of the vapors of liquids containing methyl alcohol; 90 previously unpublished cases of blindness or blindness followed by death resulting from the drinking of methylated liquids; 9 previously unpublished cases of blindness from methyl alcohol absorbed through the lungs or the skin, or both; and 82 previously unpublished case reports of fatal methyl alcohol poisonings with no associated blindness.

From a report by Baskerville, [12] it is apparent that by 1913 a dramatic increase in the industrial use of methyl alcohol was accompanied by an increased number of poisonings. The production of crude wood alcohol in the US increased from about one million gallons in 1890 to eight and one half million gallons in 1910, and the number of reported methyl alcohol poisoning cases in the US increased from almost none in 1890 to the point

where, in 1913, Baskerville was able to collect several hundred such case reports from various medical periodicals. Baskerville felt that these cases represented a small percentage of the total number because many physicians did not report cases in the scientific press and many others failed to recognize the industrial and occupational diseases of chronic methyl alcohol poisoning. [12] For an extensive summary of numerous poisoning cases from drinking wood alcohol or inhaling its vapor, the reader is referred to the Baskerville review. [12]

One of the earliest case reports of methyl alcohol poisoning in an occupational setting was by De Schweinitz [13] in 1901. He described the case of a 39-year-old man who suddenly became totally blind after a brief illness. The patient had been employed intermittently (3-4 days at a time) for 3 years as a painter and varnisher. The varnish was dissolved in methyl alcohol, and the patient stated that he generally used methyl alcohol to clean the varnish off his hands and arms, and sometimes off his face. He denied drinking the alcohol. During these 3 years, he had several times become dizzy when varnishing the insides of small articles of furniture or closets on hot days. For 2 months prior to the onset of blindness, he had worked every day as a varnisher in a shop. This was the longest period of uninterrupted exposure to the varnish during the 3-year period. He frequently noted attacks of what he called "misty vision," which disappeared 10-15 minutes after he left work. The day prior to his loss of sight, the patient was unable to work because of chills, numbness, and shooting pains in his lower extremities, and he returned home and went to bed. When he awoke the following morning, he was totally blind. Although treated by a physician, the blindness persisted for 2 weeks

whereupon the patient reported to the hospital. Upon admission, his pupils were dilated and were almost unresponsive to light. Ophthalmoscopic examination revealed clear media, but pallid discs. The veins were filled with dark blood and reduced in size. Upon treatment with pilocarpine and induction of daily vigorous sweats, the patient recovered some light sensitivity and, by the end of 2 weeks, he could distinguish objects sufficiently to walk unaided. One week later, however, his vision began to fail; when seen again approximately 3 months later, he was totally blind. The author made no attempt to estimate the quantity of methyl alcohol to which the patient had been exposed.

De Schweinitz [13] advanced the opinion that exposure to methyl alcohol (notably by percutaneous absorption and inhalation) may result in slow poisoning as a result of its gradual accumulation in the body. In turn, when a threshold level was reached, a sudden and complete blindness would occur similar to that observed in individuals who ingest great quantities of methyl alcohol. This case report indicated that blindness can occur as a result of inhalation or percutaneous absorption of methyl alcohol.

In 1917, the New York State Department of Labor [14] published a special bulletin entitled Dangers in the Manufacture and Industrial Uses of Wood Alcohol. This report enumerated cases of poisoning resulting from occupational exposure to methyl alcohol in various industries. It proposed rules designed to limit future exposures.

Perhaps as a result of increased awareness of the dangers of methyl alcohol coupled with better work practices, relatively few cases of serious poisoning (such as blindness and death) resulting from inhalation or

percutaneous absorption of methyl alcohol in an industrial setting have been found in the literature since 1920. This is in contrast to the many cases of serious poisonings resulting from the ingestion of this substance which have been continued to be reported. Some of the case reports of methyl alcohol intoxication resulting from occupational exposure between 1900 and 1921 are discussed in the Section Effects on Humans because of their current relevance. [15-19] Although these reports may well be historical in nature, the effects of methyl alcohol poisoning observed in these studies are discussed below since they clearly depict the clinical symptoms encountered with occupational exposure to methyl alcohol.

Effects on Humans

In 1958, Scherberger et al [20] described the development of a dynamic apparatus (air blender) for preparing air-vapor mixtures of known concentrations for various compounds. The concentration range of methyl alcohol vapor prepared by this apparatus was 12-1,870 ppm. Using this apparatus, the authors determined the average minimum identifiable odor level for methyl alcohol. Although exact experimental details were not presented, a photograph in the article indicated that the subjects sniffed an airstream within a few centimeters of its emission source. Using 3 subjects, the authors found that the average minimum identifiable odor level for methyl alcohol was 1,500 ppm (approximately 2,000 mg/cu m). The authors suggested these concentrations were only a rough estimate for this method, since the same subjects tested on different days showed a varying capacity for odor detection.

In 1966, May [21] determined the odor thresholds of 37 organic

solvents. Samples were prepared by evaporating a known amount of a given solvent in stoppered glass bottles. The resulting vapor concentrations were verified by gas chromatographic analysis. The subjects inhaled the air mixture directly from the bottles by taking 3 short sniffs followed by a deep respiration. The subjects first breathed samples of decreasing concentrations until no more odor could be perceived. Secondly, they breathed increasing concentrations until the odor was just barely perceptible. They then breathed increasing concentrations until they judged the odor to be distinctly perceptible. The odor thresholds reported represented the average response of 16 people, including the author and his technician, ranging in age from 30 to 63 years and equally divided as to the sexes. The average odor threshold (minimum perceptible odor) for methyl alcohol vapor was reported to be 5,900 ppm (7,800 mg/cu m), whereas the average distinct odor concentration was 8,800 ppm (11,700 mg/cu m). For comparison, the author cited an odor threshold of 2,000 ppm (2,600 mg/cu m) for methyl alcohol from a data sheet provided by the Dragerwerk Company of Lubeck. The source and purity of the methyl alcohol used in these experiments were not stated. The experimental design described does not actually eliminate the problem of olfactory fatigue. The results demonstrated, however, that with the slightest perception of an odor of methyl alcohol, the concentration of the solvent in the air already greatly exceeds the existing federal standard (200 ppm). Based on these data by May, the worker cannot rely on olfactory perception for warning purposes, except at high concentrations.

In 1959, Chao Chen-Tsi [22] reported the effects of inhaled methyl alcohol vapor on humans and animals. Using 13 subjects, the author

determined that the minimum airborne concentration of methyl alcohol that could be determined by odor ranged from 4.3 to 11.0 mg/cu m (3.3-8.5 ppm). The author also studied the effects of methyl alcohol vapor inhalation on the light sensitivity of the eye adapted to darkness in 3 subjects. The most sensitive subjects showed diminution of light sensitivity at a level of 3.3 mg/cu m (2.5 ppm), but at 2.4 mg/cu m (1.8 ppm) no such effect was detectable. On the basis of these results, the author proposed 1.5 mg/cu m (1.1 ppm) of methyl alcohol vapor in air as the maximum permissible concentration for occupational exposures.

In 1968, Ubaydullayev [23] reported on the methyl alcohol odor threshold range, on eye sensitivity to light during dark adaptation, and on alterations in the electrical activity of the cerebral cortex. For 25 subjects ranging in age from 18 to 40 years, the maximum imperceptible airborne methyl alcohol concentration was 3.9 mg/cu m (3.0 ppm) and the minimum perceptible concentration was 4.5 mg/cu m (3.4 ppm).

For eye adaptation to dark, or sensitivity to light, 3 subjects, aged 18-25, were tested. [23] The results showed that at 4.1 mg/cu m (3.1 ppm) of airborne methyl alcohol a sharp change in the subjects' eye sensitivity was observed. One individual showed a change in eye sensitivity at a concentration of 3.5 mg/cu m (2.7 ppm). No response was seen at 3.1 mg/cu m (2.4 ppm).

A group of 6 subjects most sensitive to olfactory stimuli were tested by the author [23] for alterations in activity of the cerebral cortex measured by an electroencephalograph. All 6 showed an alpha-rhythm amplitude change at a concentration of 1.5 mg/cu m (1.0 ppm) and none responded at 1.0 mg/cu m (0.8 ppm).

It is not clear whether any of these effects, reported by Chao Chen-Tsi [22] or by Ubaydullayev, [23] are to be interpreted as psychologic, physiologic, or toxicologic.

Thus, there are 2 sets of studies estimating the odor threshold for methyl alcohol: Scherberger et al [20] giving 1,500 ppm and May [21] giving 5,900 ppm (while citing 2,000 ppm as the figure suggested by the Dragerwerk Company of Lubeck) and, in marked contrast to these, Chao Chen-Tsi [22] giving 3.3-8.5 ppm and Ubaydullayev [23] giving 3.4 ppm as the minimal perceptible concentration of methyl alcohol by odor. It is difficult to reconcile such a wide discrepancy between these 2 sets of studies, even allowing for different experimental techniques. Small traces of impurities can have a very marked effect upon odor, but in the absence of any data in any of these 4 papers on the source or purity of the methyl alcohol used, the issue of impurities is a matter for conjecture.

In 1905, Jelliffe [15] reported 2 cases which he described as multiple neuritis in men engaged in shellacking furniture with shellac dissolved in methyl alcohol. Symptoms reported were paresthesia, numbing, prickling, and shooting pain in the back of the hands and forearms, in addition to edema of the arms. Both men sought medical aid promptly, and the resultant cessation of exposure probably prevented the development of serious sequelae of methyl alcohol intoxication. Jelliffe considered that these 2 cases were due to the inhalation of the vapor of the wood alcohol employed. In contrast, he described the case of a businessman who had been in the habit of drinking quite regularly, in small quantities, for a period of at least 3 months an illicit whiskey which apparently contained 35% Columbian spirits (methyl alcohol). When seen by the author, [15] the

subject was suffering from severe gastric irritability, hyperesthesia in both arms and hands, incomplete paralysis of the extensors, and wrist-drop. He also had a mild degree of ptosis of the eyelids and a restricted partial amblyopia. He recovered after 4 months of treatment but still had some residual blurring of vision. The author then lost touch with the patient. In summarizing all 3 cases, Jelliffe commented upon a postulated "greater susceptibility of the ganglion cells of the retina" to poisoning by methyl alcohol.

In 1905, Hawes [16] described a case of occupational poisoning that was attributed to the inhalation of methyl alcohol vapor. Methyl alcohol was used by a painter as a paint remover and for mixing shellac. The work consisted of pouring a quantity of methyl alcohol on furniture, rubbing the furniture with a cloth, and repeating the procedure. The painter worked in rooms no larger than 10 x 12 feet with the doors and windows kept closed. During the first day of work, he began to experience headache, nausea, weakness, and some smarting of the eyes. He completed the second day of work despite the persistence of the aforementioned symptoms as well as slight blurring of vision by the end of the second day. On the third day, as a result of increased severity of the above symptoms, he was unable to work past 8:30 AM. The painter was then hospitalized. Fifteen days after admission, on ophthalmological examination he was found to have no vision whatever. The airborne concentration of methyl alcohol in the rooms was not determined. From the author's description of this man's mode of work, he probably had had considerable skin contact with methyl alcohol, so that inhalation was probably not the sole route of absorption.

In 1912, Tyson [17] described a case of methyl alcohol poisoning in a worker who was involved in varnishing the inside of beer vats. Work was commenced on December 3, 1911, and continued on the following day with no medical complaints. On December 5, the worker experienced headache, vertigo, unsteady gait, nausea, vomiting, and acted as if intoxicated; consequently he did not work on this day. The author did not state if the subject worked on December 6. On December 7, the worker began having visual disturbances. At this time, he consulted a physician who diagnosed methyl alcohol poisoning. On December 12, an ophthalmologist made the following observations: the pupils were practically nonreactive to light, there was retinal edema, and initial vision (eccentric) was right 1/200 and left 2/200. In three weeks, his vision had improved to 20/30 in each eye. Six to 7 months later, with no additional methyl alcohol exposure, visual acuity remained stable, while the pupillary response to light remained sluggish. In addition, the author described a progressive contraction of the visual fields during the entire period of observation. Tyson also indicated that the progressive constriction of visual fields corresponded to degenerated bundles of fibers and groups of ganglion cells becoming confluent as the degenerative process spread. He also concluded that this case was produced solely by inhalation of methyl alcohol vapor. The airborne concentration of methyl alcohol to which the worker was exposed was not determined.

In a review article published in 1912, Wood [18] commented on 4 workers (one of which was the case previously described by Tyson [17]) poisoned while varnishing beer vats. Methyl alcohol was reported as a constituent of the varnish. All 4 workers had been involved in varnishing

the inside of beer vats 12-15 feet high. After the first day, one worker complained of dizziness and, after the second day, displayed an unsteady gait. On the third day, he could not return to work because of sweating, vomiting, a rash on the face and body, and progressive loss of vision. The 3 remaining workers continued to work through the third day, at the end of which they experienced varying degrees of poisoning. Two of these 3 workers died 1 and 3 days later without further occupational exposure. The remaining worker of the last 3 experienced some symptoms ("reeling, headache, etc") and apparently recovered. The airborne concentrations of methyl alcohol to which they were exposed were not reported.

In 1921, Ziegler [19] described 2 cases of methyl alcohol poisoning resulting from inhalation of the vapor. One individual experienced fading of vision and constriction of the visual fields. The author attributed this condition to exposure to methyl alcohol vapor through daily visits to a china cement factory, since analysis of the cement had shown methyl alcohol to be a constituent of the cement. The patient's vision improved after he discontinued his visits to the factory.

The second case described by Ziegler [19] involved a painter who varnished the engine room of a submarine with a methyl alcohol-based varnish. At the end of the first day, the painter experienced dizziness. On the second day, he appeared euphoric and on the third day he was nervous. He also experienced gastric pain, insomnia, and double vision. Temporary blindness occurred after termination of occupational exposure. When first seen by the author, this individual was acidotic, although the basis for the diagnosis was not reported. Three weeks following the exposure, the worker had improved considerably and his eyesight was nearly

normal. In both these cases, Ziegler claimed that the application of "negative galvanism" for prolonged periods contributed significantly to the recovery of vision, suggesting that this treatment stimulated revascularization of the optic disc. Again, no estimate was made of the airborne concentration of methyl alcohol to which the painter was exposed.

The author [19] suggested that methyl alcohol was a protoplasmic poison possessing a selective affinity for the nerve tissue of the eye, and that the proximal agents of toxicity of methyl alcohol could be formaldehyde and formic acid, both "corrosive poisons." He also proposed that the "primary and fundamental lesion" of methyl alcohol poisoning was injury to the pituitary gland. This implication of the pituitary has not, however, found support with later observers.

Thies, [24] in his 1928 report on "Eye Damage in the Chemical Industry," stated that liquid methyl alcohol coming in contact with the eyes caused severe edema of the ocular conjunctiva (chemosis) and lesions of the corneal surface that were rarely complicated and usually healed in a few days with proper treatment.

In 1941, Humperdinck [25] reported a case of methyl alcohol poisoning that occurred in a nitrocellulose plant where a worker had been exposed to damp nitrocellulose that he had unloaded, weighed, and stored. The dampened material contained 35-40% methyl alcohol. The worker had been on this job for 4 years and had not previously reported any symptoms. He became ill following the institution of wartime blackout measures which impaired plant ventilation. The initial diagnosis of pleurisy was changed retrospectively to one of acute hepatitis. He also became blind in the right eye with marked narrowing of the visual field in the left

examination of the workplace air showed methyl alcohol concentrations ranging from 1,600 to 10,900 mg/cu m (approximately 1,200 to 8,300 ppm). The diagnosis of acute hepatitis in this case appears to have been based purely upon retrospective clinical impressions, unsupported by any clinical or laboratory findings. The author suggested that methyl alcohol poisoning was confined to this one worker among a total of 23 exposed because of individual variations in susceptibility and the possibility of hereditary weakness of this worker's neuro-optical system manifested by his congenital fixation of the pupils and color blindness. The author indicated that, while relatively high airborne methyl alcohol concentrations ranging from 2,000 to 10,000 mg/cu m (1,500-7,600 ppm) may be tolerated for many years without determinable damage, however, this range of concentrations should not be considered harmless because of individual susceptibility, development of tolerance, and the cumulative effect of methyl alcohol. He therefore recommended that airborne methyl alcohol concentrations be maintained below 1,000 mg/cu m (760 ppm).

In 1957, Burk [26] described a case of occupational poisoning which he attributed to the inhalation of methyl alcohol. The worker had been employed for 7 years in a chemical-pharmaceutical factory, having spent the previous 4 years in the methyl alcohol department. In early January of 1955, the worker had complained of visual disorders, and had suffered asthenia and numbness of the hands and arms. On June 20, 1955, the worker cleaned a boiler in which crude nicotinic acid was boiled with methyl alcohol. The author reported that scraping off the residue on the inside of the boiler generated methyl alcohol fumes. During the first 50 minutes of work, the employee used a gas mask fitted in succession with 2 Type A-90

Drager respiratory filters which were impermeable to methyl alcohol. The next filter used was a Drager Type K-90, which was permeable to methyl alcohol. The latter filters were changed 4 times since they became very wet within a period of 20-30 minutes. Occasionally during the first day of scraping the boiler, the worker suffered from vertigo. During break periods in fresh air, he saw colored rings. The first day's operation required about 5 hours. The next morning, the worker became nauseated upon entering the boiler room which had been used the preceding night. Despite the nausea, the worker emptied the boiler, liberating small quantities of methyl alcohol vapor. He then suffered visual disturbances for the rest of the second day, despite the fact that he underwent no further methyl alcohol exposure. On the third day, upon entering the boiler room, the worker suffered nausea and visual disorders and was then hospitalized. Ophthalmoscopic examination showed papilledema of both eyes that began to clear after a few days. After 5 weeks, full visual acuity returned. Blood, urine, and cerebrospinal fluid tests, as well as physical examination, disclosed no abnormal findings. Formic acid, found in the urine in the first 11 weeks following the initial examination, was no longer detectable after 11 weeks. The presence of formic acid confirmed the author's belief that the toxicity was due to methyl alcohol exposure. Questioning of the patient revealed that he was in the habit of frequently washing his hands with methyl alcohol. The author [26] therefore concluded that the exposure involved a single acute intoxication by inhalation superimposed upon a chronic condition resulting from percutaneous absorption of methyl alcohol along with inhalation of low concentrations of methyl alcohol over a period of years. In his theoretical discussion of

this case, Burk [26] attributed the toxic effects of methyl alcohol to formaldehyde and formic acid, indicating that both compounds were oxidation products of methyl alcohol. The author stated that the diagnosis of methyl alcohol poisoning is sometimes very difficult, and would be more easily verified by quantitative determinations of formic acid in the urine of persons suspected of being poisoned with methyl alcohol.

The preceding 6 reports [15-17,19,25,26] all describe cases in which the mode of entry of methyl alcohol into the body was believed to be predominantly by inhalation, with the possibility in some cases of additional absorption through the skin. The following report of a collected series of cases involving infants and young children, [27] though clearly unrelated to occupational exposures, is reviewed by way of contrast as it illustrates that percutaneous absorption of methyl alcohol can lead to serious consequences, including death. In 1968, Gimenez et al [27] reported an analysis of 19 cases of children, ranging in age from 1.5 months to 4 years, who were poisoned as a result of having cloths soaked in methyl alcohol applied to their abdomens to relieve gastrointestinal troubles or other unspecified complaints. There were 2 additional cases reviewed in which both methyl and ethyl alcohols had been employed in this way, making a total of 21 cases. Although absorption of methyl alcohol via the respiratory tract was possible in these cases, the fact that the cloths were held in place by rubber baby pants would favor percutaneous absorption of the alcohol as the significant route of exposure. The length of time between application and onset of symptoms of intoxication was 1-13 hours (7 1/4 hours average). The early signs of intoxication were described by the authors as central nervous system depression with 13 children having

exhibited severe respiratory depression and 11 of these having con
Blood pH in the 21 patients ranged from 6.4 to 7.38 (normal: [28]), indicating acidosis in most cases. Twelve of the 21 child
of cardiac or respiratory arrest 2-10 days after hospital admission. The
survivors recovered without apparent permanent damage. Papilledema and
ocular fundus bleeding were observed in 2 of the infants who subsequently
died. Abdominal skin lesions were present in 5 patients, 3 of the
erythematous type and 2 of the scaling type. The authors [27] commented
that while there was no relationship between methyl alcohol blood levels as
tested in 11 children (57-1,130 mg%) and prognosis, there was a
relationship between the initial blood pH and the subsequent course of the
illness. In general, treatment consisted of administering sodium
bicarbonate, glucose, ethyl alcohol, fluids, and electrolytes. Other forms
of treatment included peritoneal dialysis, exchange transfusion, mechanical
respiration, and the administration of anticonvulsant drugs. It must be
pointed out that the absorptive properties of the skin of infants are
probably different from those of adults and consequently infant
susceptibility to, and manifestations of, methyl alcohol intoxication may
not parallel those seen in adults.

The New York State Department of Labor bulletin on the industrial
dangers of methyl alcohol [14] also reported several cases of dermatitis.
While uncommon, several cases of dermatitis of the hands were reported in
hat factories where shellac dissolved in methyl alcohol was used to stiffen
hats. In several Panama hat factories where shellac was dissolved in
methyl alcohol and where the workers' hands were in direct contact with the
solution, only one case of dermatitis was found.

The studies discussed in the remainder of this section are concerned with methyl alcohol absorption, elimination, and metabolism in the human. The effect of ethyl alcohol on the metabolism and elimination of methyl alcohol and the explanation of why ethyl alcohol administration is effective in preventing or ameliorating some of the symptoms of acute methyl alcohol intoxication in humans will also be examined.

In 1949, Agner et al [29] reported on the successful treatment of methyl alcohol intoxication in humans with ethyl alcohol. Three workmen ingested unknown quantities of methyl alcohol. Of these 3, only one became intoxicated and about 12 hours later, he vomited and complained of losing his vision. He was admitted to the hospital the following day and lapsed into a coma within 1 hour after admission. In spite of iv administration of bicarbonate and ethyl alcohol, he died 23 hours after admission. Upon admission of this patient to the hospital, his 2 drinking companions were also admitted and examined. Neither showed signs of methyl alcohol poisoning, and they were discharged the same day pending analysis of blood samples for methyl alcohol content. One showed a blood methyl alcohol concentration of 40 mg/100 ml and never displayed signs or complained of symptoms of poisoning. The other, however, had a blood methyl alcohol concentration of 236 mg/100 ml. The authors found that, on the day the latter patient ingested the initial methyl alcohol, he had also consumed an additional 100-150 ml of brandy not known to have been adulterated. Upon leaving the hospital the following morning, he consumed an additional 200-300 ml of brandy (again not known to be adulterated) before being rehospitalized that afternoon. This patient was also treated with bicarbonate for a low alkali reserve. During the next 8 hours, his blood

methyl alcohol concentration decreased only slightly, and he remained clearheaded and lucid. However, when the blood level of methyl alcohol began to decrease, the patient showed signs of motor unrest, as well as unresponsive pupils and slowness of speech. He also complained of blurred vision. An initial oral dose of 60 ml of ethyl alcohol was administered, followed every hour by additional 10-20 ml doses. Blood methyl alcohol concentration was measured every 2-3 hours. During the 10 hours immediately prior to ethyl alcohol administration, the blood concentrations of methyl alcohol decreased from approximately 210 to about 140 mg/100 ml. However, in the 24-hour period following the initiation of ethyl alcohol therapy, the level of methyl alcohol in the blood decreased to about 80 mg/100 ml. The blood methyl alcohol concentration remained nearly constant at this level for approximately 8 hours after the ethyl alcohol therapy was discontinued. The concentration of methyl alcohol in the blood then continued to decline for the next 24 hours, at which point it was no longer detectable. Within 2 hours after the first administration of ethyl alcohol, the patient became clearheaded and the motor unrest and ocular symptoms disappeared. The authors [29] concluded that the visual and other symptoms of methyl alcohol intoxication observed in this patient were caused by toxic products resulting from the oxidation of methyl alcohol rather than by methyl alcohol itself. The administration of ethyl alcohol at a level sufficient to maintain a concentration of 1.0 mg/ml in the blood caused a retardation or cessation of this oxidation, and thus inhibited the toxic action of the methyl alcohol metabolites. The authors also noted that, while the patient had a low alkali reserve, he was not acidotic; yet he showed symptoms of methyl alcohol poisoning. The authors commented that

this observation was contrary to the belief of other investigators that acidosis is the cause of methyl alcohol-poisoning symptoms. Additionally, the authors advocated treating methyl alcohol poisoning with ethanol in addition to treating acidosis.

In 1952, Leaf and Zatman [30] reported on experiments in which 5 male volunteers ingested 2.5-7.0 ml of methyl alcohol diluted to 100 ml with water. These amounts of methyl alcohol corresponded to doses of 29-84 mg/kg. Two blood samples were taken from 3 subjects, 2-5 hours after the ingestion. Urine was collected frequently for 11-16 hours following methyl alcohol administration. Both the blood and urine samples were analyzed for methyl alcohol by a colorimetric method based on the oxidation of methyl alcohol to formaldehyde and formation of a colored complex with a modified Schiff's reagent. The results of this experiment indicated that under these conditions methyl alcohol was rapidly absorbed from the gastrointestinal tract. The maximum methyl alcohol concentration in the urine was achieved approximately one hour after ingestion and then decreased exponentially. The ratio of blood to urine methyl alcohol concentrations remained almost constant for the 3 subjects in which it was determined, and the authors [30] concluded that the change in the concentration of methyl alcohol in the urine was an accurate indicator of the change in methyl alcohol concentration in the body. At the levels used in this experiment, the concentration of methyl alcohol in the urine declined to control values within 13-16 hours after ingestion. Leaf and Zatman [30] also stated that only 0.4-1.2% of the ingested methyl alcohol was eliminated unchanged in the urine and that the elimination of unchanged methyl alcohol in the expired air accounted for a similar fraction of the

dose, although the experimental evidence supporting the latter statement was not given.

In another experiment in the same study, [30] 2 male volunteers ingested 15 ml of ethyl alcohol and 4 ml of methyl alcohol simultaneously. They then ingested 10 ml of ethyl alcohol every hour for the next 7 hours. The same individuals served as their own controls in a previous experiment in which they ingested only 4 ml of methyl alcohol. Urine was collected hourly and analyzed for methyl alcohol. The maximum urinary methyl alcohol concentrations for those individuals who ingested both methyl alcohol and ethyl alcohol were 8.82 and 9.20 mg/100 ml, compared to values of 6.05 and 5.50 mg/100 ml when methyl alcohol alone was ingested. Moreover, the total amount of methyl alcohol excreted unchanged in the urine in the first 7 hours after ingestion was 107.1 mg and 125.5 mg (3.7 and 3.96% of the administered dose respectively) when both methyl alcohol and ethyl alcohol were ingested, whereas only from 18.2 to 30.8 mg (0.57-0.97% of the administered dose) was excreted unchanged in a similar time period after ingestion of 4 ml methyl alcohol alone. The authors [30] concluded that in humans ethyl alcohol interfered with the normal oxidation of methyl alcohol, causing more of it to be excreted unchanged in the urine. Moreover, according to the authors' conclusion, higher concentrations of methyl alcohol in the blood are maintained in the presence of ethyl alcohol at any given time after absorption, as compared to concentrations achieved in the absence of ethyl alcohol.

Leaf and Zatman [30] studied the absorption of methyl alcohol via the respiratory route. Two human male volunteers were exposed on several different occasions to methyl alcohol vapor at concentrations of from 650

to 1,430 mg/cu m (approximately 500-1,100 ppm). These exposures took place in a 22.9-cu m capacity room, where desired concentrations were achieved by evaporating known quantities of methyl alcohol on a hot plate in the draft of a fan. Concentrations were verified by analyzing air samples collected at frequent intervals during and after exposure for methyl alcohol content. Using urinary methyl alcohol concentrations as an index of methyl alcohol absorption, the authors concluded that the rate of absorption was proportional to the concentration of the vapor inhaled. Exposure to methyl alcohol vapor at a concentration of 1,430 mg/cu m (approximately 1,100 ppm) for 2 1/2 hours resulted in a urinary methyl alcohol concentration of 2.56 mg/100 ml. Exposure periods were not sufficiently long to determine whether the rate of excretion would increase to equal the rate of absorption. The authors remarked that an exposure period of 3-4 hours was all that could be reasonably tolerated, but did not specify whether the direct effect of methyl alcohol or personal discomfort due to the design of the experiment was the reason for the time limitation. From their studies, Leaf and Zatman [30] did calculate what they believed to be a safe inhalation dose for methyl alcohol for an 8-hour work period. They calculated the threshold of intoxication for these two workers as 2,800 ppm (3,670 mg/cu m) and 3,000 ppm (3,930 mg/cu m) respectively, and using an arbitrary safety factor, they therefore recommended a standard of 300 ppm (390 mg/cu m).

In 1953, Kendal and Ramanathan [31] studied the excretion of formate (an oxidation product of methyl alcohol) in humans. The same 2 adult males studied 4 years earlier by Leaf and Zatman [30] ingested 4 ml of methyl alcohol (approximately 50 mg/kg body weight) diluted to 100 ml with water.

In one set of experiments, methyl alcohol was ingested by itself, whereas in another, 15 ml of ethyl alcohol was ingested simultaneously with methyl alcohol, and at hourly intervals thereafter, 10 ml of additional ethyl alcohol was consumed for 5 hours. Urine was collected every 1-2 hours for about 12 hours following administration. Samples were analyzed for methyl alcohol by the method used by Leaf and Zatman, [30] and for formate by the method of Bastrup, [32] which is based on the oxidation of formate to carbon dioxide with mercuric chloride. When the volunteers ingested 4 ml of methyl alcohol without ethyl alcohol, they excreted 36 mg of methyl alcohol and 41 mg of formic acid in the first 6 hours following the ingestion. On the other hand, when the volunteers ingested ethyl alcohol with the methyl alcohol, they excreted 69 mg of unchanged methyl alcohol and no measurable formic acid during the same 6-hour period. For the period from 6 to 12 hours after simultaneous methyl alcohol and ethyl alcohol ingestion, the volunteers excreted 12 mg of formic acid as opposed to only 7 mg of formic acid in the experiment without ethyl alcohol. The authors [31] interpreted the results to indicate that ethyl alcohol interfered with the oxidation of methyl alcohol to formic acid, resulting in decreased urinary excretion of formic acid and an increased urinary excretion of unmetabolized methyl alcohol during the initial 6-hour period. During the second 6-hour period after ethyl alcohol administration ceased, however, the formic acid excretion actually increased, presumably as a result of an uninhibited methyl alcohol oxidation process. Another significant conclusion of these authors was that the kidneys must have a considerable power of concentrating formate.

In vitro studies have been carried out on highly purified preparations of alcohol dehydrogenase (ADH) isolated from human livers. [33,34] In the first study, both methyl and ethyl alcohols were found to be substrates for this enzyme system. [33] In the second study, [34] it was demonstrated that the affinity constant of human ADH for methyl alcohol as a substrate was only 1/30 of that for ethyl alcohol. Neither of the studies [33,34] reported any in vitro experimental data on competitive inhibition between ethyl and methyl alcohols for human ADH. However, in the first report, Von Wartburg et al [33] implied that ethyl alcohol would inhibit the oxidation of methyl alcohol by ADH when both substrates were available to the enzyme, and this may explain the efficacy of giving ethyl alcohol in cases of methyl alcohol poisoning. In the second study, Blair and Vallee [34] indicated that ethyl alcohol may act as a competitive inhibitor of methyl alcohol and thereby may protect against methyl alcohol toxicity in vivo. Furthermore, a study by Goodman and Tephly [35] showed that the human hepatic catalase-peroxidase system has relatively little oxidizing activity with respect to methyl alcohol in vitro, but rather oxidation proceeds through an alcohol dehydrogenase system. Thus, these in vitro studies [33-35] provide a reasonable explanation for the mechanism of action of ethyl alcohol in the studies cited previously [29-31] which indicated that ethyl alcohol is capable of blocking the oxidation of methyl alcohol in vivo. For more information concerning the pharmacology of ethyl alcohol (which includes its metabolism by alcohol dehydrogenase and other enzyme systems) the review by Ritchie [36] is recommended.

In 1971, Majchrowicz and Mendelson [37] described a study in which 19 adult male volunteers were confined in a hospital research ward, fed a

standard daily 2,000-calorie diet with multivitamin supplements, and permitted to consume up to 32 ounces/day of either bourbon (50% ethyl alcohol) or 50% USP ethyl alcohol (grain alcohol) on a spontaneous drinking regimen for a period of 10-14 days. The subjects remained confined under observation for 7-10 days after the drinking period. Fingertip blood samples were taken every morning during the drinking and observation periods. These samples were analyzed by gas chromatography for ethyl alcohol, methyl alcohol, acetaldehyde, and acetone. During the predrinking observation period, blood methyl alcohol concentrations were always less than 0.1 mg/100 ml. After one day of drinking bourbon or grain alcohol, blood methyl alcohol concentrations ranged from 0.1 mg/100 ml to 0.2 mg/100 ml, and methyl alcohol concentrations ranging from 1.1 mg/100 ml to 2.7 mg/100 ml were achieved by the last day of the drinking period. In the postdrinking period, blood methyl alcohol concentrations remained relatively constant until blood ethyl alcohol concentrations dropped below 20 mg/100 ml, at which point blood methyl alcohol concentrations began to decline. In general, the blood methyl alcohol concentration increased and decreased in concert with blood ethyl alcohol concentration, although the changes were not simultaneous. The authors also determined the concentration of methyl alcohol in the bourbon (40-55 mg/liter) and in the grain alcohol (approximately 1 mg/liter). Using the known amount of bourbon consumed and assuming an even distribution of methyl alcohol throughout the body water, body weight of 70 kg, and no loss due to metabolism or excretion, the concentration of methyl alcohol was calculated to be 0.06 mg/100 g of body water after one day and 0.84 mg/100 g of body water after 14 days. Only negligible quantities of methyl alcohol would

have been exogenously introduced by the ingestion of grain alcohol. Since the average bourbon drinker excreted more methyl alcohol per 100 ml of urine than would theoretically have been present in the same amount of body water, the authors suggested that most of the methyl alcohol in the bourbon drinker and virtually all of the blood methyl alcohol in the grain alcohol drinker arose from endogenous sources, and in the absence of ethyl alcohol, the rate of metabolism and excretion of endogenously produced methyl alcohol were sufficient to prevent its accumulation in the body. In their discussion, the authors indicated that blood concentrations of ethyl alcohol higher than 20 mg/100 ml seemed to effectively block the oxidation of methyl alcohol in vivo. This in turn resulted in a buildup of endogenously produced methyl alcohol, which was reversed only after blood ethyl alcohol concentrations dropped below 20 mg/100 ml. The authors, taking into consideration their experimental findings and those of other investigators, suggested that ethyl alcohol may inhibit the oxidation of methyl alcohol in vivo by competing (competitive inhibition) for the alcohol dehydrogenase system. It is conceivable, therefore, that chronic alcoholics might exhibit measurable concentrations of methyl alcohol in the blood or urine even though they have not been exposed to methyl alcohol.

In summary, an integration of in vitro [33-35] and in vivo studies [29-31,37] indicates that in humans methyl alcohol is oxidized primarily by alcohol dehydrogenase. The results discussed in the section on Animal Toxicity, however, suggest that in nonprimates methyl alcohol is oxidized primarily by the catalase-peroxidase system.

Epidemiologic Studies

In 1912, Tyson [17] described a factory in New York City in which 25-30 young women worked in a 20 x 50 foot room polishing wooden lead pencils with a varnish solution containing methyl alcohol. During damp or cold weather, the windows of this room remained closed in order to maintain the quality of the finished pencils. All of the women in the room experienced headaches and an unspecified number exhibited what the author termed gastric disorders. One woman missed 8 weeks of work because of chronic gastritis. Two cases from the same work area were reviewed by Tyson. The initial symptoms of a 30-year-old woman described in the first case were headache, vertigo, weakness (unspecified), and nausea without vomiting. She also had dizziness and obscuration (sic) of vision while working. The woman stated that the symptoms occurred principally during the day when the windows were closed. After working about 3 hours, she experienced blurring of vision, changes in color perception, and the symptoms mentioned previously. After half an hour in fresh air, the symptoms subsided. The same condition then occurred in the afternoon. Upon examination, her optic discs were hyperemic, the edges were blurred, and the veins were dilated. The other case was similar in that, approximately 3 hours after beginning work, the woman would on certain days experience frontal headache, dizziness, and nausea. At times, she experienced what she called a mist before her eyes. She was examined initially because of failing vision. The eye examination showed pallor, blurring, and edema of the discs, as well as dilated retinal veins. Upon questioning, both patients stated that they used methyl alcohol on occasion to cleanse their skin. The author suggested that the visual disturbances or loss of function were related to

adverse effects on nerve fibers and ganglion cells of the retina. No measurements of methyl alcohol concentration in the workroom air were reported.

Included in the New York State Department of Labor's special 1917 bulletin on the dangers of the industrial use of methyl alcohol [14] was a study of a shop in New York City where the employees dyed artificial flowers by dipping them in methyl alcohol solutions of aniline dyes. Physical findings were noted in 20 workers including dermatitis, anemia, nearsightedness, and conjunctivitis. Anemia and nearsightedness have not been reported elsewhere as signs of methyl alcohol intoxication. There was no mention in this report of headache, dizziness, nausea, or visual disturbances other than nearsightedness. Although the methods of sampling and analysis were not described, the report stated that analysis of the room air revealed a methyl alcohol concentration of 200 ppm by weight. The failure to describe sampling and analytical methods, the expression of air concentrations as a weight ratio, and the lack of comment on the possibility of skin contact make the relationship between the effects noted and the airborne concentrations reported of doubtful significance.

In 1938, Greenburg et al [38] published the results of a study of a plant in New York in which 19 workers operated steam presses in order to fuse shirt collars made of cellulose acetate and cotton impregnated with a solvent consisting of 3 parts acetone and 1 part methyl alcohol. Two air samples collected at the breathing level in the center of the workroom over a 2 1/2 hour period revealed methyl alcohol concentrations of 22 and 25 ppm and acetone concentrations of 40 and 45 ppm. The authors did not mention how the samples were taken or how they were analyzed. The employees

examined had been engaged in this operation for a period ranging from 9 months to 2 years. Physical examination, including neurological tests, detected no abnormal findings and the ocular fundi appeared normal. No visual disturbances were reported. Blood findings on all 19 were essentially normal and urinary analysis on 17 revealed nothing of significance other than a positive test for acetone. The blood tests performed included hemoglobin concentration, red cell count, reticulocyte count, total and differential white cell counts, platelet count, bleeding and coagulation times, red cell fragility, erythrocyte sedimentation rate, and serum bilirubin. The urine was examined microscopically for casts, and determinations of protein, sugar, and acetone content were made. The authors concluded [38] that these airborne concentrations of methyl alcohol and acetone were apparently not high enough to cause or produce adverse changes. While no effects were seen at 22-25 ppm of methyl alcohol, the presence of acetone in the air and in the urine precludes any definitive conclusion regarding possible adverse effects of methyl alcohol alone at these levels because of the remote possibility that acetone may interfere with the metabolism of methyl alcohol.

In 1955, Kingsley and Hirsch [39] reported that an unspecified number of employees at the Sandia Laboratory, Albuquerque, New Mexico, complained of frequent and recurrent headaches. According to the authors, all of the people affected worked in the immediate vicinity of direct process duplicating devices. These duplicating devices used different brands of duplicating fluids containing 5-98% methyl alcohol. The other ingredients in the duplicating fluids were not identified. The authors stated that those individuals situated closer to the machines experienced more severe

headaches; those who actually operated the equipment suffered the most; and that, with the onset of cold weather, when the doors and windows were closed, the severity and frequency of the headaches increased.

Air sampling was performed by what the authors [39] referred to only as standard air sampling techniques. Moreover, the method of analysis for methyl alcohol was not reported. Results revealed that air concentrations of methyl alcohol in the breathing zone of the workers ranged from 15 ppm (20 mg/cu m) to 375 ppm (490 mg/cu m) and varied with the concentrations of the methyl alcohol in the duplicating fluids. Air samples taken 10 feet from the duplicating machines showed concentrations of 100 ppm (130 mg/cu m) which, depending on the extent of ventilation, persisted for up to 4 hours. The authors indicated that the concentrations were generally in excess of 200 ppm but less than 375 ppm. As a result of this study, there was a change in the duplicating fluids used (selecting those with a lesser concentration of methyl alcohol), and the duplicating devices were moved to areas with better ventilation. The authors [39] failed to mention whether these measures had any effect on the headaches of the workers. This study may imply that methyl alcohol vapor in the air in concentrations in the range of 200 to 375 ppm may cause headaches. However, the presence of other volatile substances arising from the other ingredients in the duplicating fluid (the other ingredients of various brands of fluids used ranged from 2 to 95% of the total) could have contributed significantly to the symptoms encountered.

In 1953, Bennett et al [40] reported on a study of 323 individuals who ingested various quantities of bootleg whiskey in Atlanta, Georgia, over a 5-day period in October 1951. An analysis of the contaminated

whiskey showed that it contained 35-40% methyl alcohol by weight and less than 4% ethyl alcohol. The procedure for analysis of the contaminated liquor was not given by the authors.

Of the 323 individuals involved in this incident, [40] 41 died. The smallest amount of ingested alcohol that caused death was 3 teaspoons (approximately 15 ml) of 40% methyl alcohol, while one individual consumed 1 pint (approximately 500 ml) of the same mixture and recovered. Upon admission to a hospital, 115 patients were acidotic with CO₂-combining capacities less than 20 meq, as compared to the normal range of 24-30 meq. [40] In most cases, the latent period between ingestion of the alcohol and the onset of toxic symptoms was about 24 hours. The longest observed lag was slightly more than 72 hours, while in one instance visual symptoms developed only 40 minutes after one individual drank about half a pint of whiskey. Several patients had visual disturbances in less than 6 hours. Although the authors indicated that medical records were incomplete, they gave the following description of symptoms:

Visual disturbances - All of the 115 patients who were overtly acidotic on admission had some degree of visual impairment. More than half of the patients whose plasma bicarbonate was within normal limits when first examined had noticed at least transient difficulty in seeing. The most frequent complaint was blurred or indistinct vision.

Central nervous system manifestations - Headache was a complaint in 62% of the patients and dizziness occurred in 30% of those interviewed in detail. Complaints of weakness or general malaise were frequent. Many moribund or severely acidotic patients were stuporous or comatose, and several had repeated, sometimes terminal, convulsions. Many patients had

some degree of amnesia for the events preceding their admission to the hospital. Two patients, both severely acidotic and admitted in a maniacal state, suffered total amnesia for their actions over the period of mania.

Gastrointestinal symptoms - Nausea and vomiting occurred in 52% of those patients whose symptoms were recorded. Persistent vomiting, however, was only noted in one individual. At the time of oral treatment with a sodium bicarbonate solution, diarrhea was recorded in 10% of the cases, but constipation was a common complaint after several days in the hospital.

Pain - Apart from the headache discussed under central nervous system manifestations, 67% of the hospitalized patients complained of excruciating upper abdominal pain.

Dyspnea - Despite the severity of acidosis in many patients, dyspnea was not a major complaint in any case. Twenty-five percent of the acidotic patients had some degree of respiratory distress at some time during their illness. True Kussmaul respirations were unusual even in severely acidotic patients, occurring only in about 25% of the patients whose plasma bicarbonate was less than 10 meq/liter.

In addition to these symptoms, physical findings were described as follows:

General - Skin pallor was observed in the white patients, but no distinct discoloration was observed in the majority of the patients who were black. Body temperature was normal in the vast majority of patients.

Eyes - Dilation of the pupils and sluggish or absent reaction to light and accommodation were present in most of the cases. Photophobia was not prominent and the eyeballs were not tender to pressure. On ophthalmoscopic examination, eyeground changes characterized as hyperemia

of the optic disc and retinal edema were seen in most patients with acidosis. The severity of these eyeground changes was found to correlate better with acidosis than any other clinical finding. True papilledema was not seen.

Cardiovascular symptoms - The pulse rate was increased in only 7 cases. Blood pressure appeared to be unaffected by the poisoning.

Abdominal examination - Abdominal muscles were very rigid and tender.

Neurologic signs - Confusion, amnesia, lethargy, stupor, and deep coma were seen, as well as acute mania in the 2 cases already mentioned. Six patients, all of whom died within minutes of admission, were in deep coma with signs suggestive of meningitis.

Cause of death - The primary cause of death in acute cases was respiratory failure.

The authors indicated that, when plasma bicarbonate levels were restored to normal by alkalinization, the patients experienced a rapid relief of most of their symptoms. Moreover, the authors emphasized the importance of prompt massive alkalinization by iv administration in severe cases of poisoning by methyl alcohol since prognosis was associated with the severity of acidosis. Table III-1 illustrates the correlation between severity of acidosis and mortality.

Laboratory findings - Hemoglobin concentrations, hematocrits, and total and differential white cell counts were within normal limits. Urinalysis was performed on 43 patients on admission; there was albuminuria in 21 cases and acetonuria in 10. Urinary pH in acidotic patients was invariably between 4.5 and 5.5, rising with treatment. Apart from the acidosis, the most striking finding was an elevation of serum amylase to

TABLE III-1

MORTALITY IN TREATED PATIENTS*

	No. of patients	% mortality
Total patients	323	6.2
Acidotic: CO ₂ -combining power less than 20 meq	115	19.0
Severely acidotic: CO ₂ -combining power less than 10 meq	30	50.0

*These figures do not include patients who died at home

From Bennett et al [40]

levels of over 300 units in 14 of 21 patients tested. The authors felt that this finding could be associated with the frequency of pancreatic necrosis found at autopsy in this series.

Autopsy findings - The authors concluded from their pathologic findings that there was nothing pathognomonic concerning the lesions encountered as a result of methyl alcohol poisoning. Findings included variable cerebral edema with meningeal and subarachnoid petechiae, congestion of the lungs, epicardial hemorrhages, occasional mild fatty infiltration of the liver, gastritis, and general congestion of the abdominal viscera. In 13 of 17 autopsies reviewed (10 of which were from the 1951 outbreak and 7 from patients who had died from methyl alcohol poisoning in 1946) pancreatic necrosis was observed. This necrosis was described by the authors as being secondary to vascular injury and hemorrhage. Based on the complaint of upper abdominal pain, the occurrence

of elevated serum amylase levels, and the microscopic findings of pancreatic necrosis, the authors concluded that acute hemorrhagic pancreatitis resulted from acute methyl alcohol intoxication. Reports of acute hemorrhagic pancreatitis following methyl alcohol poisoning other than by the oral route have not been found.

Animal Toxicity

In 1942, Sayers et al [41] exposed 4 dogs (3 male and 1 female) to methyl alcohol vapor at concentrations of 450-500 ppm (590-650 mg/cu m) for 8 hours/day, 7 days/week, for 379 days. The dogs were exposed in a continuously ventilated (8 air changes/hour) chamber. High purity industrial methyl alcohol was supplied to gauze ribbons in the chamber at a constant rate using a chemical proportioning pump. Calculated methyl alcohol vapor concentrations were verified by trapping the methyl alcohol contained in a known volume of air in 100 ml of water. The methyl alcohol concentration of the water was then determined using a wet chemical colorimetric method based on the oxidation of methyl alcohol to formaldehyde and the subsequent production of a purple color upon addition of Schiff's reagent. Twenty-eight days into the experiment, the female was mated to 1 of the exposed males and had a litter of 5 pups on the sixty-second day after breeding. One of the pups accidentally died shortly after birth. The 4 surviving pups were exposed in the same manner as the other dogs for the remainder of the experiment.

Laboratory hematologic determinations (RBC count, differential WBC, platelets, hemoglobin content, and coagulation time) were made before (9 samples) and during (28-30 samples) the exposure, and blood chemistry

determinations (nonprotein nitrogen, creatinine, and sugar) were made before (3 samples) and during (9 samples) the exposure period. All results were within control limits. Thirteen ophthalmoscopic examinations on each adult dog (5 preexposure and 8 during exposure) indicated no significant or abnormal eye changes due to exposure. The pups were similarly examined 3 times and showed no evidence of impaired vision. All the adult dogs either maintained their preexposure weights or gained weight. The pups also gained weight normally. Gross and microscopic examinations at autopsy revealed no deviations from usual minor abnormalities except for some (severity not described) inflammation of the meninges of the brain in 5 animals. Microscopic examination of the brain of 3 animals was essentially normal; however, 5 showed changes in the brain, attributed to intercurrent disease based on examination of controls and other unexposed dogs. The concentration of methyl alcohol in the blood at the end of an 8-hour exposure generally ranged between 10 mg and 15 mg/100 ml of blood, but on certain occasions concentrations as high as 52 mg/100 ml were found. This study [41] is one of the few in which animals of any species were exposed to methyl alcohol under conditions which approximate those expected in an industrial exposure. The lack of interpretable findings as well as the relatively small number of animals exposed allow few definite conclusions about chronic methyl alcohol intoxication. Moreover, as will be discussed later, the course of acute methyl alcohol intoxication is different in dogs and humans and, thus, the results of experiments on dogs have limited relevance to possible adverse effects on humans.

In 1955, Gilger and Potts [42] published the results of a study of the comparative toxicity of methyl alcohol in rats, rabbits, dogs, and

rhesus monkeys. Administration of methyl alcohol (reagent grade 99.5% pure) was accomplished by gavage in all except 4 rabbit experiments where it was injected iv. Prior to oral administration, the methyl alcohol was dissolved in either water or aqueous sucrose solution in varying proportions depending on the size of the animal and its tendency to vomit the administered solution. After administration, the animals were observed for clinical signs of intoxication, blood samples were taken at variable intervals so that CO₂-combining capacities (a measure of acidosis) could be determined, and repeated ophthalmoscopic examinations were performed on the rabbits, dogs, and monkeys.

Among 23 rats receiving 4.75 g of methyl alcohol/kg of body weight, (as a 50% aqueous solution) approximately 70% died. [42] Blood samples were obtained at 4.5, 27, and 47 hours after administration of 4.5 g of methyl alcohol/kg (as a 50% aqueous solution) to 9 male rats. CO₂-combining capacities ranged from 47 to 80 volumes % in these samples. The authors stated that no acidosis was seen although they did not report control or normal CO₂-combining capacities for rats.

Three rabbits given 2.1 g of methyl alcohol/kg of body weight (as a 30% aqueous solution) died between 24 hours and 3 days after oral administration. [42] One additional rabbit died in less than 24 hours after being given 3.5 g of methyl alcohol/kg orally (as a 50% aqueous solution). The results of ophthalmic investigation revealed no fundus changes. The results of acidosis studies in treated rabbits were ambiguous in that CO₂-combining capacities ranged from 19 to 56 volumes % in untreated animals. None of the methyl alcohol-treated rabbits exhibited a CO₂-combining capacity below the normal range at any time.

Among 9 dogs administered [42] oral doses of methyl alcohol ranging from 2.5 g/kg to 9.0 g/kg, 7 survived while 1 dog receiving 4.0 g/kg died between 29 and 46 hours after administration and another receiving 9.0 g/kg died 28-42 hours after administration. The highest nonlethal dose was 8.0 g/kg. It is not clear whether these doses are absolute methyl alcohol or a dilute solution. None of the dogs exhibited ophthalmoscopic changes. CO₂-combining capacities dropped below the approximate range of normal values (42-54 volumes %) in only 2 of the 9 treated dogs. The surviving dog which was administered the highest dose, 8.0 g/kg, had the largest decrease in CO₂-combining capacity. Its CO₂-combining capacity returned to normal approximately 55 hours later. In neither case did the CO₂-combining capacity decrease to levels similar to those observed in monkeys which were poisoned with methyl alcohol.

Six rhesus monkeys received oral doses of from 1.0 to 8.0 g methyl alcohol/kg. [42] Two monkeys receiving 1.0 and 2.0 g methyl alcohol/kg, respectively, survived while 4 monkeys receiving 3.0, 4.0, 6.0, and 8.0 g/kg, respectively, died. One monkey receiving 8.0 g/kg body weight died between 6 and 23 hours, while the monkey receiving 6.0 g/kg body weight died 29 hours following the administration of methyl alcohol. Two of the fatally poisoned monkeys showed definite eyeground changes while the other 4 monkeys showed no changes on ophthalmoscopic examination. Changes included retinal hemorrhage in one monkey and blurring of the disc, venous engorgement, and possible hyperemia of the disc in the other. Of the 6 monkeys, the one receiving the lowest dose (1.0 g/kg) did not become acidotic and the one receiving the highest dose (8.0 g/kg) died before the CO₂-combining capacity was determined. The remaining monkeys all became

severely acidotic with minimum CO₂-combining capacities ranging from 9.8 to 15.9 volumes %. Three died while acidotic at doses of 3.0, 4.0, and 6.0 g/kg, respectively. The CO₂-combining capacity in the other monkey (2.0 g/kg) had returned to normal 21 days after administration.

Gilger and Potts [42] concluded from their studies that the results of oral administration of methyl alcohol to rats, rabbits, and dogs differed from those reported on humans in 4 important areas, namely, lethal dose, time course of development and signs of intoxication, eye effects, and acidosis. The authors also concluded that, following intoxication with methyl alcohol, the responses of primates more closely approximated human responses than did those of nonprimates. An extensive review of the literature dealing with the oral toxicity of methyl alcohol in humans and nonprimates was supportive of their conclusion. The authors concluded that the approximate lethal oral dose of methyl alcohol in humans (0.85-1.4 g/kg) was 1/3 the equivalent dose in monkeys and 1/9 the equivalent dose in rats. Moreover, nonprimates exhibited severe early intoxication with narcosis lasting until death whereas primates showed much less early intoxication followed by a symptomless latent period, then by sickness and death. The only eye changes observed with certainty in nonprimates were early pupillary changes and corneal opacities following exposure keratitis. Some monkeys, however, and many humans developed partial or complete blindness accompanied by eyeground changes such as hyperemia of the optic discs and venous engorgement. Finally, humans and monkeys often developed severe acidosis (CO₂-combining capacity less than 20 volumes %) after methyl alcohol ingestion; this condition was rare in nonprimates and occurred only at near lethal or lethal doses.

Also in 1955, Roe [43] reviewed the literature on the toxicity and metabolism of methyl alcohol and correlated this with his clinical experience. Great emphasis was placed on the importance of acidosis in human patients but not in animals. In humans, treatment of methyl alcohol poisoning with sodium bicarbonate to control acidosis and ethyl alcohol to inhibit the rate of methyl alcohol oxidation was very effective, whereas, in animals this was useless or deleterious. Roe [43] recognized that acidosis in humans was important and that there was a fundamental difference in methyl alcohol metabolism by humans and by animals.

In 1962, Cooper and Kini [44] reviewed the biochemistry of methyl alcohol poisoning with emphasis on enzyme systems. This and their own experimental research led to the conclusion that, while in lower animals methyl alcohol was metabolized to formaldehyde by catalase, in monkeys it was alcohol dehydrogenase, and not the catalase system, that was primarily responsible for methyl alcohol oxidation.

The recent review of the literature including their own research by Tephly et al [45] summarizes and expands on the above concepts. They make a distinction, not between animals and humans but between lower animals and primates, since rhesus monkeys share with humans the phenomena of acidosis and ocular toxicity. The reasons for these differences are not clear, but there are established differences in metabolic mechanisms. In rats, methyl alcohol is oxidized primarily by a catalase-peroxidase system, while in monkeys and humans it is oxidized by a liver alcohol dehydrogenase system. It appears that animal species, other than perhaps monkeys, are inadequate models for elucidating the nature of methyl alcohol poisoning in humans. Therefore, the extensive literature relating to the adverse effects of

parenterally administered methyl alcohol in nonprimate animals will not be treated in this document because the results of those studies are likely to bear little relevance to the occupational hazards to human health resulting from exposure to methyl alcohol. However, a few studies on the effects of methyl alcohol in monkeys and the irritant effects of externally applied methyl alcohol on lower animals will be described in this section. In addition, several studies which indicate a different route of methyl alcohol metabolism in primates and nonprimates will be discussed. For more information on the effects of parenterally administered methyl alcohol on nonprimate animals, the reader is referred to the somewhat old, but very thorough, review by von Oettingen. [46]

In 1931, McCord [47] studied the effects of methyl alcohol by skin absorption and inhalation in monkeys, rabbits, and rats. Skin absorption experiments were carried out by clipping the abdominal hair of the animals, then applying several layers of gauze padding to the clipped area which were held in place with bandages covered by rubber dam and secured with a canvas corset. Methyl alcohol was applied to the gauze pads with a hypodermic needle and syringe, thus precluding concurrent inhalation of the methyl alcohol. He described the results of the skin absorption experiments by stating that all animals subjected to the action of any amount of methyl alcohol by skin absorption had died. The lowest lethal dose was 0.5 ml/kg for one monkey. The author reported that rabbits were far less susceptible to methyl alcohol poisoning by this route than monkeys and rats. In a study of the effects of continuous administration of methyl alcohol, a known amount was dropped onto or injected into the gauze pads 4 times/day. All such treated monkeys displayed dilated pupils within 2

hours after one such administration of 1.3 mg/kg of methyl alcohol. The minimum lethal dose was a total of 4 administrations of 0.5 ml/kg methyl alcohol in one day, and the author concluded that sufficient methyl alcohol could be absorbed through the skin to cause death and that the threshold for immediate danger in monkeys was below the minimum lethal dose. By extrapolation, he concluded that 2.5-3.0 ounces (77.5-93 ml) of methyl alcohol applied once to an average-sized man under conditions favoring retention would be conducive to harm and would be undesirable; the assumptions used to arrive at these figures were not stated. The lack of specific information as to the exact skin area covered by the gauze pads as well as a confusing presentation of results (the author did not include detailed protocols in the report) detract from the quantitative value of this paper.

In order to determine the effects of methyl alcohol by inhalation, McCord [47] placed the animals in gassing chambers for from 1 to 18 hours. Air was continuously pumped through the chamber at a known rate. Methyl alcohol vapor was generated by dripping liquid methyl alcohol at a constant rate on a heated glass plate. Concentrations were calculated from the known volume of methyl alcohol evaporated in the chamber and the volume of air moved through the chamber, but air samples were not analyzed to confirm the validity of these calculations. Thus the true airborne concentrations may have been lower than those reported. The results of these studies were not presented in a clearly tabulated form. However, the author noted that the threshold of danger was well below 1,000 ppm, a concentration that led to the death of some of the animals. He reported marked differences in individual and species susceptibility. Thus, one monkey survived an

extended exposure (exact time not reported) of 5,000 ppm while another died "promptly" upon exposure to 1,000 ppm. The average rabbit was said to be far more resistant to methyl alcohol vapor than the average monkey. McCord stated that it was not unusual to observe monkeys which were totally blind, as determined by both general observation and ophthalmoscopic examination, recover their sight and display no signs of intoxication. Corneal opacity in both rats and rabbits occurred early in the clinical manifestations of poisoning, presumably in contrast to the slower development of blindness in monkeys. As a result of the incomplete reporting of quantitative results in this study, it is difficult to assess the validity of the author's inference that the vapor from 1 ounce (approximately 30 ml) of methyl alcohol even over a period of 2-3 days constitutes a threat to human life.

In 1961, Cooper and Feig [48] described a study in which methyl alcohol was administered to rhesus monkeys of both sexes. The expressed purpose of this study was to identify the organic acid or acids believed to appear in increased amounts in the urine of monkeys and humans as a result of methyl alcohol poisoning. Unfortunately, no human material was available during the course of this study. Twelve monkeys were used in this experiment with 8 being reused from 1-5 times. After oral administration of the methyl alcohol, the monkeys were observed at frequent intervals for spontaneous activity, maintenance of equilibrium, resistance to handling, and response to visual and other stimuli. Twenty-four hour urine samples, collected both before and after administration, were analyzed for organic acids. Serum bicarbonate levels were determined as a measure of metabolic acidosis.

The results of this study [48] were unexpected in that the monkeys used did not respond to methyl alcohol intoxication like humans or like the monkeys in the study by Gilger and Potts. [42] In the first place, all monkeys receiving methyl alcohol at doses of 6 g/kg or less survived; the LD50 was found to be in the range of 7-9 g/kg. Secondly, the clinical course of fatal poisoning was narcosis followed by death with no asymptomatic latent period. Thirdly, only one monkey displayed a transient blindness 4 days after receiving 9 g of methyl alcohol/kg. Finally, only one out of three monkeys appeared to develop a definite metabolic acidosis. This animal, however, failed to demonstrate an increased excretion of urinary organic acids as did all the other monkeys in this experiment. The authors suggested that the monkey was an animal model intermediate between nonprimates and humans as it demonstrated characteristics similar to both nonprimates and humans. The originally expressed purpose of this study was to identify the acids found in the urine of humans following methyl alcohol poisoning using rhesus monkeys. Cooper and Felig, [48] however, found no significant increase in urinary excretion of organic acids 24-72 hours following ingestion of methyl alcohol.

A series of normal aliphatic alcohols were tested for comparative irritant potential in 4 rabbits by Renkonen and Teir. [49] Methyl, ethyl, propyl, butyl, amyl, hexyl, heptyl, and octyl alcohols in doses of 10 and 35 mg dissolved in water or paraffin oil at a constant volume dose were injected intracutaneously, and the animals were observed for skin reactions. Measurements of skin reactions were performed 24 hours after injection of the alcohols. At 10 mg of methyl or ethyl alcohol in water, no skin reactions were seen. The other alcohols, however, all elicited a

skin reaction. At 35 mg of the alcohols in water, methyl alcohol elicited a 9-sq mm skin reaction, ethyl alcohol a 47-sq mm skin reaction, and propyl alcohol a 75-sq mm skin reaction. At least on the basis of tests on rabbits, it would appear that methyl alcohol is not a significant skin irritant.

In a range-finding test designed to show the potential for chemical substances to produce chemical burns of rabbit corneas, methyl alcohol was classified as grade 3 by Carpenter and Smyth. [50] The total grading scale ran from 1 to 10. An example of compounds in grades 1, 5, and 10 are ethylene glycol, acetone, and sodium hydroxide, respectively.

The remaining studies discussed in this section explore the enzymatic pathways of methyl alcohol metabolism in the animal systems studied and show that the primary pathway of methyl alcohol metabolism (although not the products) is different in nonprimates and primates.

In 1964, Tephly et al [51] studied the effect of ethyl alcohol and 1-butanol on the metabolism of ¹⁴C-labeled methyl alcohol in rats. The rats were given 1 g/kg of ¹⁴C-labeled methyl alcohol ip and monitored in metabolism cages. Methyl alcohol was oxidized at a constant rate of 24 mg/kg/hr for the first 28 hours. At the end of 36 hours, 77% of the methyl alcohol had been converted to ¹⁴C-labeled carbon dioxide and 24% of the administered dose was excreted unchanged. Approximately equal amounts were excreted unchanged by pulmonary and combined urinary and fecal routes. When an equimolar amount of ethyl alcohol was injected with the 1 g/kg ¹⁴C-methyl alcohol, there was a 55%-decrease in the amount of total ¹⁴C-labeled carbon dioxide excreted in the first 90 minutes following administration. The authors concluded that the enzyme systems responsible for the

metabolism of methyl alcohol were inhibited by ethyl alcohol, but a more likely interpretation is that ethyl alcohol preempted the metabolic activity of this enzyme system. The authors cited previous in vitro studies which indicated that the isolated catalase-peroxidase system had an equal affinity for methyl and ethyl alcohols whereas the affinity of the purified alcohol dehydrogenase system was 10-50 times greater for ethyl alcohol than for methyl alcohol. The authors [51] considered this to be evidence that the catalase-peroxidase system was primarily responsible for methyl alcohol metabolism in rats. At a molar ratio of 8:1 methyl alcohol to ethyl alcohol, there was no inhibition of ethyl alcohol metabolism. The authors concluded from this that the metabolic pathway for ethyl alcohol oxidation plays an insignificant role in the rat for the oxidation of methyl alcohol.

Additionally, 1-butanol was studied for its effect on the oxidation of ¹⁴C-ethyl and ¹⁴C-methyl alcohol. [51] In vitro studies cited by the authors indicated that 1-butanol had a greater affinity for ADH than ethyl alcohol; however, 1-butanol was a poor substrate for the catalase-peroxidase system. The in vivo experimental results revealed that 1-butanol was a potent inhibitor of ethyl alcohol metabolism and a poor inhibitor of methyl alcohol metabolism. Furthermore, the authors studied the effect of 3-amino-1,2,4-triazole (AT), an inhibitor of catalase, on the oxidation of ¹⁴C-methyl alcohol and ¹⁴C-ethyl alcohol. Pretreatment of rats with 1 g/kg AT ip 1 hour prior to methyl alcohol administration decreased methyl alcohol oxidation by about 50%. AT had virtually no effect on ethyl alcohol oxidation. In summary, the authors concluded from the results of all these studies that the catalase-peroxidase system in the

rat played a major role in the oxidation of methyl alcohol and was not primarily responsible for the oxidation of ethyl alcohol.

In 1968, Makar et al [52] published a comprehensive study on the mechanism by which methyl alcohol is metabolized by monkeys in vivo. Six young rhesus monkeys were used repeatedly throughout the study. They received ^{14}C -methyl alcohol injected ip. The monkeys were divided into 2 groups. In order to determine the effect of dose size on oxidation, one group received 1 g/kg and the second group received 6 g/kg. At the 1 g/kg dose, ^{14}C -methyl alcohol was oxidized at the rate of 37 mg/kg/hour between the first and the fourth hours. During this period, the rate of ^{14}C -labeled carbon dioxide formation was linear. The animals receiving 6 g/kg oxidized the alcohol at a rate of 47 mg/kg/hour during the same time interval. Thus, the oxidation rates of the 2 doses were significantly different. In the animals receiving the higher dose of ^{14}C -methyl alcohol, 49% of the methyl alcohol was oxidized to ^{14}C -carbon dioxide, 35% was removed by pulmonary excretion as unchanged methyl alcohol, and 16% was removed via the kidneys as unchanged methyl alcohol.

The effect of ethyl alcohol on ^{14}C -methyl alcohol oxidation and methyl alcohol on ^{14}C -ethyl alcohol oxidation in monkeys was also studied. [52] Varying amounts of ethyl alcohol were injected with a constant dose of ^{14}C -methyl alcohol (0.5 g/kg), and ^{14}C -labeled carbon dioxide was collected at intervals over a 4-hour period. When equimolar quantities of the 2 alcohols were used, methyl alcohol oxidation was reduced 90% throughout the entire period of observation. These results are in contrast to the results of Tephly et al [51] in rats as described above where an equimolar dose of ethyl alcohol caused a 55%-reduction in methyl alcohol

metabolism. The results of the equimolar doses of the alcohols indicated that the peroxidative system is not the primary metabolic pathway for methyl alcohol in the monkey. If it were so, inhibition of methyl alcohol oxidation should have been around 50%. These findings suggested that the alcohol dehydrogenase system, or possibly a system other than the peroxidative system, was responsible for methyl alcohol oxidation in the monkey.

In another study, [52] the effect of 1-butanol on 14C-methyl alcohol metabolism in the monkey was observed. In vitro studies cited by the authors showed that, compared with ethyl alcohol, the reactivity of 1-butanol was greater for the alcohol dehydrogenase system. Moreover, 1-butanol was less reactive with the peroxidase system than either ethyl or methyl alcohol. With a molar ratio of 14C-methyl alcohol to 1-butanol of 1:0.5, the oxidation of methyl alcohol was inhibited 63% during the first 90 minutes following dosing. This finding is in contrast to the results of the rat experiments described earlier [51] in which 1-butanol did not noticeably affect methyl alcohol metabolism. This again supported the view that for monkeys the alcohol dehydrogenase, or some system not involving catalase, is the primary metabolic pathway for methyl alcohol oxidation.

Makar et al [52] referred to one of their earlier studies in which the effects of inhibition by AT on hepatic catalase in the rat were examined. Intraperitoneal administration of AT to rats was shown to reduce the oxidation of methyl alcohol by 50% in vivo. However, in this study, [52] when 5 monkeys received AT prior to 14C-methyl alcohol, there was no significant drop in methyl alcohol metabolism. This suggested to the authors that the catalase peroxidase system was important in the oxidation

of methyl alcohol in the rat but did not play a significant role in the monkey.

Clay and coworkers [53] administered methyl alcohol to rats, rhesus monkeys, and pigtail monkeys. Acidosis developed consistently in pigtail monkeys (at 2-4 g/kg ip) but in only 1 of 4 rhesus monkeys (at 4 g/kg ip) and not at all in rats. Using the pigtail monkey as the animal model of choice for other experiments, several studies were performed. Blood ions and pH were measured in pigtail monkeys injected ip with methyl alcohol 4 g/kg as a 20% solution in physiological saline. Blood bicarbonate (pCO₂ and total CO₂) and pH decreased over the period 7.5-21 hours, glucose increased moderately and formate increased markedly. There were also significant increases in lactate, alpha-hydroxybutyrate, beta-hydroxybutyrate, alpha-ketobutyrate, acetoacetate, p-hydroxyphenylacetate, and p-hydroxyphenyllactate; however, these increases accounted for only a small part of the increases in blood anions, with formate constituting the major, almost total, constituent replacing blood bicarbonate. In another experiment, a specific inhibitor of hepatic alcohol dehydrogenase, 4-methylpyrazole (50 mg/kg by vein) was administered 30 minutes prior to methyl alcohol (4 g/kg ip) and every 6 hours thereafter. Under these circumstances, there were no significant decreases in blood pH or other signs of toxicity during the 48-hour observation period. These experiments give additional support to the evidence that methyl alcohol in primates is primarily metabolized by alcohol dehydrogenase and then further oxidized to formate which is the principle cause of acidosis.

The well-designed studies of Tephly et al, [51] Makar et al, [52] and Clay et al [53] present strong evidence that different enzyme systems are

primarily responsible for the oxidation of methyl alcohol in rats and monkeys and that the pathway in monkeys more closely resembles the pathway in humans as previously discussed in this chapter. The cited evidence also indicates that the nature of methyl alcohol poisoning in monkeys more closely resembles that in humans than in nonprimates. It is tempting to speculate that this similarity is a result of the similar metabolic pathways in these species. No direct evidence supporting this speculation has been found, however, and the exact reasons why humans are affected differently by methyl alcohol than nonprimates remain unknown.

Correlation of Exposure and Effect

Well-documented studies that correlate environmental levels of methyl alcohol with observed toxic effects have not been found in the literature, nor have any long-term epidemiologic studies of chronic low-level occupational exposure been found.

Effects seen from either of the 2 most common routes of occupational exposure (inhalation and percutaneous absorption) include: headache [14,16,17,39]; dizziness [13,19]; nausea [16,17,26]; vomiting [17]; weakness (unspecified) [16]; vertigo [17,26]; chills [13]; shooting pains in the lower extremities [13]; unsteady gait [17]; dermatitis [14]; multiple neuritis characterized by paresthesia, numbness, prickling, and shooting pain in the back of the hands and forearms, as well as edema of the arms [15]; nervousness [19]; gastric pain [19]; insomnia [19]; acidosis [19]; and formic acid in the urine. [26] Eye effects, such as blurred vision, [16,17] constricted visual fields, [17,19,25] blindness, [13,25] changes in color perception, [17] double vision, [19] and general visual

disturbances [17] have been reported. Eye examinations have shown sluggish pupils, [13,17] pallid optic discs, [13] retinal edema, [17] papilledema, [26] hyperemia of the optic discs with blurred edges and dilated veins. [17]

The study by Bennett et al [40] showed similar symptoms resulting from ingestion. These are acidosis, headache, visual disturbances, dizziness, nausea and vomiting, severe upper abdominal pain, dilated and nonreactive pupils. Eyeground examinations showed hyperemia of the optic discs and retinal edema. The eyeground changes were almost always found in acidotic patients. This finding is suggestive of a correlation between acidosis and visual disturbances. However, a number of patients, with and without acidosis, complained of visual disturbances. Additionally, blood tests showed elevated serum amylase levels in 14 of 21 patients. This finding in conjunction with complaints of upper abdominal pain and pancreatic necrosis seen at autopsy led the authors [40] to conclude that hemorrhagic pancreatitis resulted from acute methyl alcohol intoxication. However, reports of acute hemorrhagic pancreatitis by parenteral routes have not been found.

Direct skin contact with methyl alcohol has been said to cause dermatitis, [14] erythema, and scaling. [27] The reported variability in susceptibility [14] is probably largely because of variations in time of contact with methyl alcohol; it is evident that sufficient dermal contact with any lipid solvent such as methyl alcohol has the potential for causing skin irritation.

Direct contact of methyl alcohol with the eyes resulted in chemosis and superficial lesions of the cornea which were rarely of a serious

nature. [24] This conclusion was supported by the findings of later studies on rabbits, [50] which showed that methyl alcohol was a mild eye irritant.

Many of the signs and symptoms of intoxication attributed to either the ingestion, inhalation, or percutaneous absorption of methyl alcohol are not specific to methyl alcohol. Thus, for example, headache, dizziness, nausea and other gastrointestinal disturbances, weakness, vertigo, chills, behavioral disturbances, and neuritis can be caused by a wide range of chemical and physical stresses on the organism. Therefore, these signs and symptoms may be of little use in diagnosing methyl alcohol poisoning. The characteristic signs and symptoms of methyl alcohol poisoning in humans, then, are the various visual disturbances and severe metabolic acidosis which appear to result from overexposure to methyl alcohol by any route. Chronic exposure at relatively low levels of methyl alcohol may have effects other than those resulting from acute exposure; however, no studies have been found that would support this speculation.

The presence of a characteristic asymptomatic latent period following ingestion of methyl alcohol, prior to the development of acidosis and/or visual disturbances in humans and in some nonhuman primates, suggests that these effects are caused by a metabolite of methyl alcohol rather than by the alcohol itself. Evidence for a metabolite of methyl alcohol acting as the proximal toxic agent is the fact that toxic manifestations can be attenuated by the administration of ethyl alcohol, [29] a compound that has been shown to inhibit the oxidation of methyl alcohol in vivo. [30,31,37]

As a result of the critical role which the metabolism plays in the course of human methyl alcohol intoxication, it is clear that factors which

affect that metabolic pathway will also affect the severity and course of the methyl alcohol intoxication. The amelioration of methyl alcohol poisoning by ethyl alcohol [29] is one example. The individual variations in activity of the alcohol dehydrogenase systems probably account for the variation in the individual responses observed with methyl alcohol poisoning. In their study of an epidemic of methyl alcohol poisoning, Bennett et al [40] noted what they called an extreme variation in individual response to a given amount of methyl alcohol in that one individual died after ingesting approximately 15 ml of a 40% methyl alcohol solution and another survived after ingesting 500 ml of this same solution. This wide variability in individual susceptibility to ingested methyl alcohol has also been noted by others, [11] and reviewed by Cooper and Kini. [44]

Although not as clearly documented, there appears to be a similar individual variability among persons exposed to methyl alcohol by inhalation or percutaneous absorption, both in the type of symptoms manifested and in their severity. For example, Wood [18] described the cases of 4 men who were employed together as varnishers of beer vats. One felt dizzy after the first day and could not continue past the second day. Another did not develop symptoms until the third day. The remaining 2 worked through the third day but subsequently died without returning to work. In Tyson's study of the pencil-varnishing operation, [17] all the women in the room presumably had similar exposures but only 2 sought medical treatment for visual disorders. The results of one inhalation study [47] using rhesus monkeys revealed individual susceptibility differences in that one animal died during exposure to 1,000 ppm methyl

alcohol whereas another survived an exposure to 5,000 ppm.

Quantitative data are not available which might indicate at what concentration in the air methyl alcohol constitutes a threat to human life. McCord [47] reported that exposure of one monkey to methyl alcohol at 1,000 ppm for an unspecified length of time was lethal, but the lack of reported experimental detail leaves this result open to question.

Humperdinck [25] described a case in which an employee experienced diminution of vision which was associated with chronic exposure in the workplace to concentrations of methyl alcohol in the range of 1,600-10,900 mg/cu m (1,200-8,300 ppm).

Leaf and Zatman [30] reported that, when human volunteers were exposed to methyl alcohol concentrations of 650 to 1,430 mg/cu m (500-1,100 ppm), 3-4 hours of exposure were all they could reasonably tolerate. The authors did not make it clear, however, whether further exposure could not be tolerated because of the direct effect of methyl alcohol vapor or because of the conditions of the experiment.

Kingsley and Hirsch [39] reported that the frequency and severity of persistent headaches in employees of the Sandia Laboratories appeared to be a function of the proximity of their workplace to direct process duplicating machines which used methyl alcohol-based duplicating fluid. Air samples in the vicinity of the duplicating machine operations in the workers breathing zone revealed concentrations of methyl alcohol ranging from 15 to 375 ppm (20-490 mg/cu m), while air samples 10 feet from the machines revealed concentrations of approximately 100 ppm (130 mg/cu m). As stated by the authors, concentrations were usually in excess of 200 ppm (260 mg/cu m) and less than 300 ppm (490 mg/cu m).

In 1917, the New York State Industrial Commission [14] made a survey of the artificial flower industry, in which methyl alcohol was used as a dye solvent. In one factory, the airborne level of methyl alcohol was found to be 200 ppm W/V. In many instances, the odor was noticeable at a distance of 75 feet from the dipping and drying operation. Exposure to methyl alcohol in this environment was said to result in dermatitis, anemia, nearsightedness, and conjunctivitis. As previously discussed in the section on Epidemiologic Studies, it seems doubtful that exposures at 200 ppm of methyl alcohol were responsible for the effects noted.

Greenburg et al [38] reported on the health effects of 19 men employed in the fused-collar industry for a period of 9 months to 2 years. The airborne concentrations of methyl alcohol and acetone to which these workers were simultaneously exposed were 22-25 ppm and 40-45 ppm, respectively. Physical examination including ophthalmoscopic examination performed on these men revealed no significant findings which might be related to methyl alcohol exposure.

Chao Chen-Tsi [22] stated that airborne methyl alcohol at a concentration of 3.3 mg/cu m (2.5 ppm) caused a diminution of light sensitivity in the most sensitive human subjects whereas methyl alcohol at a concentration of 2.4 mg/cu m (1.8 ppm) had no such effect.

Ubaydullayev [23] indicated that airborne methyl alcohol at a concentration of 3.5 mg/cu m (2.7 ppm) caused a change in one human subject's sensitivity to light during dark adaptation whereas a concentration of 3.1 mg/cu m (2.4 ppm) had no effect. In addition, all 6 human subjects exposed to airborne methyl alcohol at a concentration of 1.5 mg/cu m (1.1 ppm) showed changes in the alpha-rhythm amplitude of their

EEG's, whereas 1.0 mg/cu m (0.77 ppm) was a no-effect level.

Unfortunately, it is difficult to assess the validity of the results reported both by Chao Chen-Tsi [22] and by Ubaydullayev [23] since neither author provided any specific information as to the source and purity of the methyl alcohol used, how the subjects were exposed to methyl alcohol, how methyl alcohol concentrations were determined, how the human responses were measured, and what statistical methods were used to treat the experimental data. Moreover, even if adverse effects do occur at relatively low concentrations of methyl alcohol, it has not been clearly established whether subtle changes in EEG patterns or light sensitivity can be classed as adverse health effects. As discussed in the section Effects on Humans, it seems doubtful that these represent adverse changes of exposure at low concentrations of methyl alcohol.

Chao Chen-Tsi [22] and Ubaydullayev [23] reported odor thresholds for methyl alcohol which also were studied by Scherberger et al [20] and May. [21] Ubaydullayev [23] reported a minimal perceptible concentration of methyl alcohol of 3.4 ppm while May [21] reported an odor threshold of 5,900 ppm. May's study has the advantage of being thoroughly described; it used a relatively large number of subjects. If, in fact, the odor threshold for methyl alcohol is in the neighborhood of 5,900 ppm, it is clear that methyl alcohol may not be detectable by odor at concentrations which might pose a threat to human health.

A summary of available data would seem to indicate that chronic exposure to air concentrations of methyl alcohol in a range of 1,200-8,300 ppm can lead to impaired vision. [25] Concentrations probably in excess of 200 ppm may lead to persistent, recurring headaches. [39] On the other

hand, occupational exposures at air levels of 25 ppm [38] during an 8-hour working day apparently may be endured without harmful effects.

No human or experimental mammalian studies have been found to evaluate the possible mutagenic, teratogenic, or carcinogenic effects of methyl alcohol. In a study [54] in grasshoppers, *Oxya velox* Fabricius, 0.3% methyl alcohol injected in the vicinity of the testes produced an incidence of 3.5% chromosomal aberrations in testicular tissue, but examination of the stages of spermatogenesis was not performed.

No aberrations were observed in grasshoppers injected with distilled water. Saha and Khudabaksh [54] did not report any evidence for the induction of permanent aberrations in germ cell lines or for the inheritability of the observed aberrations. In view of the fundamental differences in genetic mechanisms, the utility of the grasshopper in quantitatively predicting inheritable germinal or somatic mutations in humans is questionable.

IV. ENVIRONMENTAL DATA AND ENGINEERING CONTROLS

Sampling and Analysis

Airborne methyl alcohol concentrations can be measured directly with chemical indicator tubes [55] by passing a known volume of gas through the sampling tube, thus producing a stained zone on the indicating portion of the tube; the length of the stained zone is a measure of the concentration. As these tubes tend to give very high results, [55] they are suitable only for the approximate assessment of airborne concentrations and qualitative surveys. Moreover, they are not specific to methyl alcohol since they are also used for ethyl alcohol. [55]

Smith and Pierce [56] have shown that certain plastic bags will retain up to 97% of the methyl alcohol in air sampled for up to 120 hours at concentrations from 100 to 400 ppm. This particular sampling method is bulky and is applicable for peak and ceiling determinations and for TWA determinations if a sufficient number of small samples or a sufficiently slow sampling rate is used.

Rogers [57] reported that a midget impinger, containing 10 ml of distilled water as a sampling medium, had a collection efficiency of approximately 92% for methyl alcohol at concentrations of 200 and 400 ppm (260 and 520 mg/cu m). These sampling efficiencies were reported at sampling rates of 1-3 liters/minute. When a fritted glass bubbler was also tested using 10 ml of distilled water, the collection efficiency was approximately 91% and 96% for methyl alcohol concentrations of 200 and 400 ppm (260 and 520 mg/cu m), respectively. The major disadvantage of the fritted bubbler is that it limits the sampling rate to around

1 liter/minute. Additionally, the collection efficiency of water was slightly impaired when the methyl alcohol concentration of the solution exceeded 5 mg/10 ml. [57] A significant disadvantage of collection in a liquid system is that sample loss can occur from spillage or evaporation during the actual sampling, or in transit for analysis.

Silica gel has been tested and used by some investigators for sampling solvent vapors. [58,59] One significant problem of this method with regard to methyl alcohol sampling is that the presence of high water vapor concentrations (85-95%) in air reduces the collection efficiency when the total amount of silica gel in the sampling tube is 150 mg (100 mg adsorbing section; 50 mg backup section). [58] The use of larger tubes containing 850 mg silica gel (700 mg adsorbing section; 150 mg backup section) has succeeded in effectively preventing the interference of water vapor in the collection process over a range of 100-1,000 ppm methyl alcohol. [60] An obvious advantage of collection on a solid medium such as silica gel is that sample loss cannot occur from spillage during sampling or in transit for analysis.

Infrared spectrophotometry has been successfully used for the qualitative analysis of various compounds, including alcohols. For quantitative analysis, however, there are practical problems, such as cell width and complexity of spectra which could cause overlapping of the spectral components of the sample, and narrow peaks which could cause deviations from Beer's law, as mentioned by Skoog and West. [61]

Numerous colorimetric methods for quantitative analysis of collected samples of methyl alcohol have been used. [57,62-66] These methods are based on the following principle: methyl alcohol is oxidized to

formaldehyde with potassium permanganate. The formaldehyde is then reacted with Schiff's reagent [57,62,63,65,66] or rosaniline solution [64] to produce an easily recognizable and stable color. In recent years however, gas chromatography has become the more prevalent method for the analysis of organic solvents. [58,67-70] This method is particularly desirable since it is capable of analyzing for other substances simultaneously with methyl alcohol.

Appendices I and II present the recommended methods for the sampling and analysis of methyl alcohol. Briefly, the sample is drawn through a silica gel tube, desorbed with distilled water [60] and analyzed by gas chromatography. [69] The sampling device is small and portable. The sample can then be analyzed by means of a rapid, relatively specific instrumental method, with minimal interferences, most of which can be eliminated by altering chromatographic conditions.

Environmental Levels

Little information has been found concerning levels of atmospheric methyl alcohol in industry. In 1917, the New York State Industrial Commission [14] made a survey of the artificial-flower industry, in which methyl alcohol was used as a dye solvent. In one factory, the airborne level of methyl alcohol was found to be 200 ppm W/V. In many instances, the vapor was noticeable at a distance of 75 feet from the dipping and drying operation. Since the minimum detectable odor for methyl alcohol, as reported by May, [21] was 5,900 ppm, it would appear that the airborne concentrations of methyl alcohol were quite high.

In their study of the wood-heel industry, Elkin's and Hemeon [71]

supervised a survey of 13 of the 41 establishments engaged in the wood heel-covering business. Air analysis in 8 of the 13 plants yielded the following average methyl alcohol concentrations: plant (1), 780 ppm (1,020 mg/cu m); plant (2), 475 ppm (622 mg/cu m); plant (3), 365 ppm (478 mg/cu m); plant (4), 320 ppm (419 mg/cu m); plant (5), 210 ppm (275 mg/cu m); plant (6), 185 ppm (242 mg/cu m); plant (7), 180 ppm (236 mg/cu m); plant (8), 160 ppm (209 mg/cu m). With the exception of plant (4), in which only one value was given, the rest of the values were the average of 2 determinations.

In 1938, Greenburg et al [38] found airborne methyl alcohol concentrations of 22-25 ppm (29-33 mg/cu m) in well-ventilated rooms in which methyl alcohol was used to impregnate fused collars.

Goss and Vance, [72] in a survey of 5 plants using duplicating machines, reported the following average airborne methyl alcohol concentrations: plant (1), 367 ppm (480 mg/cu m); plant (2), 45 ppm (57 mg/cu m); plant (3), 572 ppm (749 mg/cu m); plant (5), 206 ppm (270 mg/cu m); and 260, 93, and 165 ppm (340, 122, and 216 mg/cu m, respectively) in 3 different departments of plant (4). Samples of duplicating fluids used were reported to contain between 45 and 85% methyl alcohol in plants (2) through (5).

Leaf and Zatman [30] investigated atmospheric conditions in a methyl alcohol-manufacturing plant. The sampling was done in 3 distinct plant areas: the synthesis plant, the distillation plant, and the stripping plant. In the synthesis plant, where the operations were completely enclosed (high-pressure manufacturing process), no methyl alcohol was found (less than 5 ppm). In the distillation plant, the air samples taken near

the sampling tray, the most likely place for an accumulation of vapor in the distillation area, contained 40-64 ppm (54-84 mg/cu m) of methyl alcohol. In the stripping plant, the airborne methyl alcohol concentrations were 80, 82, and 116 ppm (105, 108, and 152 mg/cu m, respectively).

McAllister, [73] also in a study of airborne methyl alcohol concentrations around 4 different makes of duplicating machines, reported average breathing zone concentrations that ranged from 400 to 800 ppm (524-1,050 mg/cu m). Moreover, general room air concentrations were as high as 1,000 ppm (1,300 mg/cu m). Although not clearly stated by the author, his report would indicate that these high concentrations occurred because the room was small and had poor ventilation. Subsequent sampling in a well-ventilated office with only 3 machines in operation was carried out and breathing zone samples showed methyl alcohol concentrations ranging from 155-420 ppm (200-550 mg/cu m). Air concentrations of methyl alcohol 10 feet from the machines decreased to 65 ppm (85 mg/cu m).

Dutkiewicz and Blockowicz [74] performed field studies in one of a number of plants manufacturing emulsifying agents (lanoceryt, euceryt) and the raw material used in their chemical synthesis, namely cholesterol. Methyl alcohol was used in various stages of a multistage manufacturing process. Airborne concentrations of methyl alcohol were determined at all stages of the process and at least twice at each worksite. Air samples were collected at hourly intervals during the entire work shift or for the duration of any one particular process. Average airborne concentrations were found to range from 45 mg/cu m (34 ppm) to 1,100 mg/cu m (840 ppm) depending on the worksite. In this particular plant, the worksites were

not stationary and the workers were consequently exposed to various concentrations of airborne methyl alcohol for varying periods of time.

Control of Exposure

Engineering design and work practices for operations with methyl alcohol should have as their main objectives controlling vapor concentrations, minimizing skin and eye contact, and preventing fires.

Closed systems, properly operated and maintained, should be used where practicable to achieve all 3 objectives. Where closed systems are not feasible, local exhaust systems and temperature control can be used to control methyl alcohol exposures. [75,76] It is preferable to control methyl alcohol vapor at the source, rather than by general dilution ventilation. Specific operations in which methyl alcohol is used in aerosol form, such as spraying methyl alcohol-containing materials like lacquers or varnishes, may require additional precautions. These precautions may include correct placement of exhaust hoods and air movers. Exhaust air should not be recirculated or discharged into the atmosphere in such a manner that it may reenter the work area. Guidance for the design and operation of ventilation systems can be found in Industrial Ventilation--A Manual of Recommended Practice [77] or revisions thereto, and in Fundamentals Governing the Design and Operation of Local Exhaust Systems 29.2-1971. [78] Sparkproof equipment should be used in all areas in which the possibility of ignition exists. Although respiratory protective equipment is not an acceptable substitute for proper engineering controls, it should be available for emergency purposes and for nonroutine

maintenance and repair.

Protective clothing should be worn whenever repeated or prolonged skin contact may occur. [76] Eye protection should be used in areas where splashing of methyl alcohol is possible. [76]

Although methyl alcohol is a liquid at normal air temperature, it is sufficiently volatile to create hazardous vapor concentrations in confined spaces. The vapor is flammable and will burn in open air. The lower explosive or flammability limit is approximately 6.7% or 67,000 ppm. [4]

Structures and operations should be designed to minimize the amount of methyl alcohol that may become airborne, for example, by the installation of appropriate local ventilation, thus reducing the possibility of fires. All areas in which methyl alcohol is stored should be well ventilated. Storage of large volumes of methyl alcohol should be remote from inhabited buildings or structures. [76]

V. DEVELOPMENT OF STANDARD

Basis for Previous Standards

In 1940, Bowditch et al [79] published the Code for Safe Concentrations of Certain Common Toxic Substances Used in Industry. These safety limits were used to some extent in Massachusetts as a guide to manufacturers and others interested in maintaining satisfactory working conditions. The maximum allowable concentration (MAC) for methyl alcohol was given as 200 ppm (260 mg/cu m). [79] No basis for this recommended value was furnished.

In 1945, Cook [80] reviewed the MAC's of industrial atmospheric contaminants as promulgated by a number of states (California, Connecticut, Massachusetts, New York, Oregon, and Utah), the US Public Health Service (USPHS), and the American Standards Association, now known as the American National Standards Institute (ANSI). Oregon had a MAC of 100 ppm (130 mg/cu m) for methyl alcohol. Utah's limits were 100-200 ppm (130-260 mg/cu m). The other 4 states, USPHS, and American Standards Association gave the MAC as 200 ppm (260 mg/cu m). Cook [80] also recommended a limit of 200 ppm (260 mg/cu m). The basis for this recommendation was the work of Sayers et al, [41] who observed no toxic signs or unusual behavior in 4 dogs exposed to methyl alcohol vapor at a concentration of 450-500 ppm (590-650 mg/cu m) for 8 hours daily (7 days/week) for 379 days.

ANSI's [2] acceptable concentrations for methyl alcohol in 1971 were: 200 ppm (260 mg/cu m) as an 8-hour TWA concentration limit, a ceiling concentration of 600 ppm (785 mg/cu m) for an 8-hour workday, 5-day workweek, if the TWA limit was at, or below, 200 ppm, and a maximum peak

concentration of 1,000 ppm (1,300 mg/cu m) for a duration of not more than 30 minutes if encountered not more than once a day. If such peaks occurred, they were to be taken into consideration in maintaining the overall TWA concentration. Recommendations were "based upon the present state of human experience and animal investigation"; however, the specific citations were not given other than the AIHA Hygienic Guide Series published in 1957 [81] for methyl alcohol for the peak concentration.

The most recent (1971) documentation of the methyl alcohol TLV's [82] explained the basis for the TLV of 200 ppm (called a MAC), first recommended in 1946; Cook [80] was cited in support of this TLV. It was the opinion of the TLV committee [82] that the 200-ppm value "incorporates a fairly large margin of safety against serious toxic effects." In the 1974 TLV Documentation, [83] the limit for methyl alcohol was still listed at 200 ppm (260 mg/cu m) with a "Skin" designation, which is intended to suggest the need to prevent skin contact or absorption, or that such absorption should be considered in evaluating exposures.

The current federal worker exposure standard for methyl alcohol is 200 ppm (260 mg/cu m) as a TWA concentration limit (29 CFR 1910.1000), based on the 1968 ACGIH recommendation for a TLV, which was documented in 1971. [82]

A survey [84] of occupational limits that have been set by foreign countries shows a wide variation in recommendations. In 1974, the Federal Republic of Germany had a standard of 260 mg/cu m (200 ppm); in 1973, the German Democratic Republic had a standard of 100 mg/cu m (76.4 ppm); in 1973, Sweden had a standard of 280 mg/cu m (214 ppm); in 1969, Czechoslovakia had a standard of 100 mg/cu m (76.4 ppm). In 1959 the USSR

standard was 50 mg/cu m (38.2 ppm) as a maximum permissible concentration. [85] A more recent (1972) survey [14] listed the USSR standard as 5 mg/cu m (3.8 ppm) as a ceiling. [84] The reference [84] indicates that with the exception of the USSR, the rest of the values listed for the other countries were for an 8-hour TWA.

The 1969 Documentation of MAC in Czechoslovakia [86] cited the work of Greenburg et al, [38] Sayers et al, [41] Elkins, [87] and Cook. [80] The Czechoslovakia MAC Committee did not consider the work of Sayers [41] applicable for toxicity in humans, particularly for effects on the optic nerve.

Basis for the Recommended Environmental Standard

Epidemiologic studies incorporating comprehensive environmental surveys, well-planned surveillance, a sufficient study population, and statistical analysis have not been found in the literature. It is therefore difficult to recommend an environmental limit based upon unequivocal scientific data.

Numerous effects including dizziness, [13,19,40] nausea and vomiting, [17,40] visual disturbances of various types, [17,40] acidosis, [19,40] and headache [14,16,17,39,40] have been reported following exposure to methyl alcohol by ingestion, inhalation, and percutaneous absorption. Many of these previously enumerated effects are not unique to methyl alcohol intoxication, as they can be caused by a wide range of other chemical and physical stresses. The signs and symptoms most characteristic of methyl alcohol poisoning in humans are various visual disturbances [14,16,17,19,25] and metabolic acidosis. [19,40] The relationship between

acidosis and visual disturbances may or may not be one of cause-and-effect, as was demonstrated in the study of Bennett et al [40] in which patients with and without acidosis complained of visual disturbances.

The characteristic asymptomatic latent period between ingestion of methyl alcohol and the development of toxic manifestations lends some support for the hypothesis that the metabolic products of methyl alcohol are the proximal toxic agent(s). In addition, toxic manifestations can be attenuated by the administration of ethyl alcohol, [29] a compound which has been shown to inhibit the metabolism of methyl alcohol in vivo. [30,31,37]

Direct skin contact with methyl alcohol has been reported to cause dermatitis [14,27,71] although there appears to be a marked individual variability in susceptibility.

Direct contact of methyl alcohol with the eyes is said to result in chemosis and superficial lesions of the cornea which are rarely of a serious nature. [24] This conclusion is supported by the finding that methyl alcohol was a mild eye irritant in rabbit eye tests. [50]

While not clearly documented, there appears to be a wide range of individual variability among subjects exposed to methyl alcohol by inhalation, percutaneous absorption, and ingestion. Wood [18] described the cases of 4 men who were employed together as varnishers of beer vats and thereby exposed to methyl alcohol both by inhalation and by percutaneous absorption. One man complained of dizziness after the first day and could not continue work after the second day. Another did not develop symptoms until the third day. The remaining two worked through the third day but subsequently died without returning to work. This

variability can be seen more clearly in the cases of 2 men observed by Bennett et al [40] in which one individual died after ingesting approximately 15 ml of a 40% methyl alcohol solution while another survived after ingesting 500 ml of the same solution. This wide variability in individual susceptibility to ingested methyl alcohol has also been noted by others. [11,44]

Humperdinck [25] has reported one case in which a worker suffered diminution of vision at airborne methyl alcohol concentrations ranging from 1,600 to 10,900 mg/cu m (1,200-8,300 ppm). Leaf and Zatman [30] showed that, in human volunteers, airborne concentrations of methyl alcohol from 650 to 1,430 mg/cu m (500-1,100 ppm) could only be tolerated for 3 to 4 hours. The authors [30] did not define intolerable conditions. Kinsley and Hirsch [39] reported that airborne methyl alcohol concentrations ranging from 15 ppm (20 mg/cu m) to 375 ppm (490 mg/cu m) caused severe recurrent headaches. As the authors stated, the concentration to which the workers were probably exposed was always in excess of 200 ppm with a peak concentration of 375 ppm. The New York Department of Labor bulletin [14] reported dermatitis of the inflammatory type, anemia, nearsightedness, and conjunctivitis at airborne methyl alcohol concentrations of 200 ppm (260 mg/cu m). There is, however, little evidence that anemia and nearsightedness were attributable to methyl alcohol exposure. In addition, the relationships between the effects described and the airborne concentrations reported are of doubtful significance as previously discussed in Chapter III. Greenburg et al [38] reported that no adverse health effects were seen at airborne methyl alcohol concentrations of 22-25 ppm (29-33 mg/cu m).

Chao Chen-Tsi [22] and Ubaydullayev [23] reported that airborne concentrations around 3.3-3.5 mg/cu m (2.5-2.7 ppm) caused a diminution of light sensitivity and that this effect was not seen at 2.4-3.1 mg/cu m (1.8-2.4 ppm). Additionally, Ubadullayev showed that all 6 human subjects tested at an airborne methyl alcohol concentration of 1.46 mg/cu m (1.1 ppm) showed changes in alpha rhythm amplitude as measured on an EEG, whereas 1.0 mg/cu m (0.77 ppm) did not elicit this response. As previously discussed (see Chapter III), the relative importance of these effects is questionable in standard setting.

The wide range of estimates of the odor threshold for methyl alcohol can be seen clearly from 2 sets of studies estimating the odor threshold for methyl alcohol, Scherberger et al [20] reporting 1,500 ppm and May [21] giving 5,900 ppm (while citing 2,000 ppm as the figure suggested by the Dragerwerk Company of Lubeck) and, in marked contrast to these, Chao Chen-Tsi [22] giving 3.3-8.5 ppm and Ubaydullayev [23] giving 3.4 ppm as the minimal perceptible concentration of methyl alcohol by odor. It is difficult to reconcile such wide differences, even allowing for different experimental techniques. Small traces of impurities can have a very marked effect upon odor, but in the absence of any data in any of these 4 papers on the source or purity of the methyl alcohol used, the issue of impurities is only a matter for conjecture.

No information has been found to warrant a modification of the existing federal TWA limit for exposure to methyl alcohol of 200 ppm (approximately 260 mg/cu m). In particular, no comprehensive epidemiologic studies or other significant data on the inhalation of pure methyl alcohol vapor have been found. Most of the human inhalation studies reported

involve other airborne organic compounds as well as methyl alcohol. Hence, no valid dose-response relationships concerning the inhalation of methyl alcohol vapors can presently be established. Therefore, there is no justification for changing the current TWA environmental limit of 200 ppm (approximately 260 mg/cu m) for methyl alcohol. Since the adverse effects of methyl alcohol are primarily related to its action on the central nervous system, it is possible that exposure to high airborne concentrations for brief periods may sufficiently affect attention, judgment, or perception so that, if an emergency were to occur, the worker might not take appropriate action. This suggests the need for a ceiling concentration to be observed, as a limitation on excursions above the TWA and as a limit applicable to occasional and brief use of methyl alcohol. However, after detailed consideration of the data applicable to derivation of such a ceiling, no basis from the scientific data appears. Thus, a ceiling limit of 800 ppm (1048 mg/cu m) based on a 15-minute sampling period is proposed on the basis of good practice.

It is recognized that many workers handle small amounts of methyl alcohol or work in situations where, regardless of the amount used, there is only negligible contact with the substance. Under these conditions, it should not be necessary to comply with many of the provisions of this recommended standard, which has been prepared primarily to protect workers' health under more hazardous circumstances. Concern for the workers' health requires that protective measures be instituted below the enforceable limit to ensure that exposures stay below that limit. For these reasons, the action level for methyl alcohol has been defined as worker exposure at or above half the TWA environmental limit, thereby delineating those work

situations which require the expenditure of health resources, of environmental and medical monitoring, and associated recordkeeping. Half the TWA environmental limit has been chosen on the basis of professional judgment rather than on quantitative data that delineate nonhazardous areas from areas in which a hazard may exist. However, because of nonrespiratory hazards such as those resulting from skin or eye contact or from ingestion, it is recommended that appropriate work practices and protective measures be required regardless of the air concentration.

VI. WORK PRACTICES

Work practices germane to the safe handling of methyl alcohol are the subject of several thorough documents [3,76]; however, reports of work practices specifically designed for the prevention of low level exposure to methyl alcohol have not been found. In general, the primary goal of good engineering controls and work practices should be to maintain vapor concentrations below prescribed limits, to minimize excursions and eye and skin contact, and to prevent fires.

The flash point of methyl alcohol is 54 F (12 C) [3]; it is therefore designated as a flammable liquid of Class IB in 29 CFR 1910.106 (19)(11). The lower and upper explosive limits for methyl alcohol in air at 20 C are 6.7% and 36.5% by volume. [4] Different values for the lower explosive limit have been reported and found to range from 6.0%, as reported in the hygienic guide for methyl alcohol, [88] to 7.3% given by the Manufacturing Chemists' Association. [3] Hence, fire and explosion are significant hazards associated with the storage, handling, and use of methyl alcohol. The recommended work practices are intended to ensure that no flames or other sources of ignition such as lighted smoking materials are permitted in the area where methyl alcohol is stored or handled. An acceptable margin of safety for flammable substances is 10% of the lower explosive limit (29 CFR 1917.11(a)(2) and 29 CFR 1915.11(a)(2)). Therefore, precautions against fire and explosion hazards must be taken to ensure that airborne methyl alcohol concentrations do not accumulate to, or exceed, 0.67% (6,700 ppm). Special precautions are necessary for entering vessels which may contain methyl alcohol [3] and for flame- and spark-generating

operations, such as welding, cutting, smoking, and transferring methyl alcohol. [89,90]

Ingestion of methyl alcohol can cause serious poisoning resulting in death or blindness. [11,40] In order to prevent the worker from accidentally ingesting methyl alcohol, it is essential that all containers in which methyl alcohol is kept must be properly labeled as to content, hazard, and possible health consequences if consumed. Additionally, the consumption or storage of food or beverages should not be permitted in the workplace in accordance with provisions of 29 CFR 1910.141 (g)(2) and (g)(4).

While airborne levels of methyl alcohol can be maintained below limits that are injurious to the health and safety of the workers by engineering controls, [77,78] certain situations such as spills, equipment failure or maintenance, vessel entry, etc, can occur which require special respiratory protection. The selection of the proper respiratory devices is presented in Chapter I.

Although methyl alcohol is not a primary skin irritant, prolonged or repeated contact with the liquid has produced dermatitis in a few people. [14] A greater hazard than dermatitis is severe poisoning that may occur from skin absorption of methyl alcohol, reported by Gimenez et al [27] in children. While protective clothing normally is not required, if it is needed to prevent contamination from methyl alcohol splashes or prolonged skin contact, it should be impervious to methyl alcohol. [3,76] If methyl alcohol is splashed on clothing, the methyl alcohol should be immediately washed off and the garment thoroughly dried before reuse. [3] Additionally, any affected areas of the body (except the eyes) must be

washed thoroughly with soap and water and a change of clothing provided. [3,90] The employer may wish to provide protective clothing of a fire-retardant nature, even though it is not required.

Chemosis and lesions of the corneal surface have resulted from methyl alcohol splashed in the eyes. [24] Depending on the nature of the operation, eye protection in the form of goggles or face shields should be used to protect against methyl alcohol coming in contact with the eyes. [3,91,29 CFR 1910.133] If methyl alcohol comes in contact with the eyes, they should be immediately flushed with copious amounts of water, and the patient should be examined by a physician. [76]

In summary, precautions should be exercised against fire and explosion hazards of methyl alcohol. Additionally, precautions should be taken to prevent the serious consequences from methyl alcohol due to ingestion, inhalation, or skin or eye contact. It is important that workers be informed of the hazards associated with methyl alcohol before job placement and whenever changes are made in any process that may alter their exposure. Flammability and appropriate procedures should be stressed. Appropriate posters and labels should be displayed. The US Department of Labor form OSHA-20, "Material Safety Data Sheet," or a similar OSHA-approved form, should be filled out. All employees in the methyl alcohol exposure area should know where the safety sheet is posted. Safety showers, eyewash fountains, and fire extinguishers should be located in areas where methyl alcohol splashes are likely to occur and should be properly maintained. Handwashing facilities including soap and water should be available to employees.

The safe handling of methyl alcohol depends to a great extent upon the effectiveness of employee education, proper safety instructions, intelligent supervision, and the use of safe equipment. The education and training of employees to work safely and to use the personal protective equipment is the responsibility of management. Training classes for both new and current employees should be conducted periodically to maintain a high degree of safety in handling procedures. [3]

VII. REFERENCES

1. Woodward HF Jr: Methanol, in Kirk-Othmer Encyclopedia of Chemical Technology, ed 2 rev. New York, John Wiley and Sons, 1967, vol 13, pp 370-98
2. American National Standards Institute: Acceptable Concentrations of Methanol, ANSI Z 37.14-1971. New York, ANSI, 1971, 8 pp
3. Chemical Safety Data Sheet SD-22--Properties and essential information for safe handling and use of methanol. Washington, DC, Manufacturing Chemists' Association Inc, 1970, 17 pp
4. Weast RC (ed): Handbook of Chemistry and Physics--A Ready-Reference Book of Chemical and Physical Data, ed 55. Cleveland, CRC Press, 1974, p D-85
5. Blackford JL: Methanol (methyl alcohol), in Chemical Economics Handbook. Menlo Park, Cal, Stanford Research Institute, 1974, pp 674.5021B-674.5021G
6. Gafafer WM: Occupational Diseases--A Guide to Their Recognition, publication No. 1097. US Department of Health, Education, and Welfare, Public Health Service, 1964, pp 176-78
7. Taylor P: On pyroligneous aether. Philos Mag J 60:315-17, 1822
8. Dumas J, Peligot E: [Organic chemistry--I. On a new alcohol and its compounds--extract from an article.] J Prakt Chem 3:369-77, 1834 (Ger)
9. MacFarlan JF: On methylated spirits, and some of its preparations. Pharm J Trans 15:310-15, 1855
10. Wood CA: Death and blindness as a result of poisoning by methyl, or wood alcohol and its various preparations. Int Clin 16:68-78, 1906
11. Wood CA, Buller F: Cases of death and blindness from Columbian spirits and other methylated preparations. JAMA 43:972-77,1058-62,1117-23, 1904
12. Baskerville C: Wood alcohol--A report of the chemistry, technology and pharmacology of and the legislation pertaining to methyl alcohol. New York State Factory Investigation Commission, Appendix 6, vol 2, pp 917-1042, 1913
13. De Schweinitz GE: A case of methyl-alcohol amaurosis, the pathway of entrance of the poison being the lungs and the cutaneous surface. Ophthalmic Rec 10:289-96, 1901

14. Dangers in the manufacture and industrial uses of wood alcohol, special bulletin No. 86. Albany, State of New York Department of Labor, Division of Industrial Hygiene, 1917, pp 1-17
15. Jelliffe SE: Multiple neuritis in wood alcohol poisoning. Med News 86:387-90, 1905
16. Hawes AT: Amblyopia from the fumes of wood alcohol. Boston Med Sur J 153:525, 1905
17. Tyson HH: Amblyopia from inhalation of methyl alcohol. Arch Ophthalmol 16:459-71, 1912
18. Wood CA: Death and blindness from methyl or wood-alcohol poisoning with means of prevention. JAMA 59:1962-66, 1912
19. Ziegler SL: The ocular menace of wood alcohol poisoning. JAMA 77:1160-66, 1921
20. Scherberger RF, Happ GP, Miller FA, Fassett DW: A dynamic apparatus for preparing air-vapor mixtures of known concentrations. Am Ind Hyg Assoc J 19:494-98, 1958
21. May J: [Odor thresholds of solvents for evaluating solvent odors in air.] Staub-Reinhalt Luft 26:385-89, 1966 (Ger)
22. Chao Chen-Tsi: [Materials on the hygienic standardization of the maximally permissible concentration of methanol vapors in the atmosphere.] Gig Sanit 24:7-12, 1959 (Rus)
23. Ubaydullayev R: A study of hygienic properties of methanol as an atmospheric air pollutant, in Levine BS (transl): USSR Literature on Air Pollution and Related Occupational Diseases--A Survey 17:39-45, 1968
24. Thies O: [Eye damage in chemical industries.] Zentralbl Gewerbehyg Unfallverhüt 15:303-08, 1928 (Ger)
25. Humperdinck K: [On the problem of chronic intoxication with methanol vapors.] Arch Gewerbepathol Gewerbehyg 10:569-74, 1941 (Ger)
26. Burk M: [On chronic occupational methyl alcohol intoxication.] Klin Monatsbl Augenheilkd 130:845-50, 1957 (Ger)
27. Gimenez ER, Vallejo NE, Roy E, Lis M, Izurieta EM, Rossi S, Capuccio M: Percutaneous alcohol intoxication. Clin Toxicol 1:39-48, 1968
28. Table of normal values, in Davidsohn I, Henry JB (eds): Todd-Sanforde's Clinical Diagnosis by Laboratory Methods, ed 15. Philadelphia, WB Saunders Company, 1974, Appendix 3

29. Agner K, Hook O, von Porat B: The treatment of methanol poisoning with ethanol--With report of two cases. *J Stud Alcohol* 9:515-22, 1949
30. Leaf G, Zatman LJ: A study of the conditions under which methanol may exert a toxic hazard in industry. *Br J Ind Med* 9:19-31, 1952
31. Kendal LP, Ramanathan AN: Excretion of formate after methanol ingestion in man. *Biochem J* 54:424-26, 1953
32. Bastrup J: Method for the determination of formic acid in urine. *Acta Pharmacol* 3:303-11, 1947
33. Von Wartburg JP, Bethune JL, Vallee BL: Human liver alcohol dehydrogenase--Kinetic and physiochemical properties. *Biochemistry* 3:1775-82, 1964
34. Blair AH, Vallee BL: Some catalytic properties of human liver alcohol dehydrogenase. *Biochemistry* 5:2026-34, 1966
35. Goodman JI, Tephly TR: Peroxidative oxidation of methanol in human liver--The role of hepatic microbody and soluble oxidases. *Res Commun Chem Pathol Pharmacol* 1:441-50, 1970
36. Ritchie JM: The aliphatic alcohols, in Goodman LS, Gilman A (eds): *The Pharmacological Basis of Therapeutics*, ed 4. New York, The MacMillan Co, 1970, p 141
37. Majchrowicz E, Mendelson JH: Blood methanol concentrations during experimentally induced methanol intoxication in alcoholics. *J Pharmacol Exp Ther* 179:293-300, 1971
38. Greenburg L, Mayers MR, Goldwater LJ, Burke WJ: Health hazards in the manufacture of "fused collars"--II. Exposure to acetone-methanol. *J Ind Hyg Toxicol* 20:148-54, 1938
39. Kingsley WH, Hirsch FG: Toxicologic considerations in direct process spirit duplicating machines. *Compen Med* 40:7-8, 1954-1955
40. Bennett IL Jr, Cary FH, Mitchell GL Jr, Cooper MN: Acute methyl alcohol poisoning--A review based on experiences in an outbreak of 323 cases. *Medicine* 32:431-63, 1953
41. Sayers RR, Yant WP, Schrenk HH, Chornyak J, Pearce SJ, Patty FA, Linn JG: Methanol poisoning--I. Exposure of dogs to 450-500 ppm methanol vapor in air--Report of Investigations RI 3617. US Dept of Interior, Bureau of Mines, 1942, pp 1-10
42. Gilger AP, Potts AM: Studies on the visual toxicity of methanol--V. The role of acidosis in experimental methanol poisoning. *Am J Ophthalmol* 39:63-86, 1955

43. Roe O: The metabolism and toxicity of methanol. *Pharmacol Rev* 7:399-412, 1955
44. Cooper JA, Kini MM: Editorial--Biochemical aspects of methanol poisoning. *Biochem Pharmacol* 11:405-16, 1962
45. Tephly TF, Watkins WD, Goodman JI: The biochemical toxicology of methanol, in *Essays in Toxicology*. New York, Academic Press, 1974, chap 6
46. Von Oettingen WF: The aliphatic alcohols--Their toxicity and potential dangers in relation to their chemical constitution and their fate in metabolism, bulletin No. 281. US Dept of Health, Education, and Welfare, Public Health Service, 1943
47. McCord CP: Toxicity of methyl alcohol (methanol) following skin absorption and inhalation--A progress report. *Ind Eng Chem* 23:931-36, 1931
48. Cooper JR, Felig P: The biochemistry of methanol poisoning--II. Metabolic acidosis in the monkey. *Toxicol Appl Pharmacol* 3:202-09, 1961.
49. Renkonen KO, Teir H: Studies on the local reactions of the skin to chemical compounds. *Ann Med Exp Biol Fenn* 35:67-69, 1957
50. Carpenter CP, Smyth HF Jr: Chemical burns of the rabbit cornea. *Am J Ophthalmol* 29:1363-72, 1946
51. Tephly TR, Parks RE Jr, Mannering GJ: Methanol metabolism in the rat. *J Pharmacol Exp Ther* 143:292-300, 1964
52. Makar AB, Tephly TR, Mannering GJ: Methanol metabolism in the monkey. *Mol Pharmacol* 4:471-83, 1968
53. Clay KL, Murphy RC, Watkins WD: Experimental methanol toxicity in the primate--Analysis of metabolite acidosis. *Toxicol Appl Pharmacol* 34:49-61, 1975
54. Saha AK, Khudabaksh AR: Chromosome aberrations induced by methanol in germinal cells of grasshopper, *Oxya velox* Fabricius. *J Exp Biol* 12:72-75, 1974
55. Technology Committee (GA Hedgecock, chmn), Working Party (SJ Silk, chmn): Chemical indicator tubes for measurement of the concentration of toxic substances in air--First report of a working party of the Technology Committee of the British Occupational Hygiene Society. *Ann Occup Hyg* 16:51-62, 1973
56. Smith BS, Pierce JO: The use of plastic bags for industrial air sampling. *Am Ind Hyg Assoc J* 31:343-48, 1970

57. Rogers GW: Sampling and determination of methanol in air. J Ind Hyg Toxicol 27:224-30, 1945
58. Documentation of NIOSH Validation Tests, NIOSH contract No. CDC 99-74-45. US Dept of Health, Education, and Welfare, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, 1975, pp S59-1 to S59-9
59. Feldstein M, Balestrieri S, Levaggi DA: The use of silica gel in source testing. Am Ind Hyg Assoc J 28:381-85, 1967
60. Methyl alcohol Class B, NIOSH Sampling Data Sheet #36.01. US Dept of Health, Education, and Welfare, Public Health Service, Center for Disease Control, National Institute for Occupational Safety and Health, December 15, 1975, December 16, 1975, January 26, 1976
61. Skoog DA, West DM: Fundamentals of Analytical Chemistry. New York, Holt, Rinehart and Winston, 1963, pp 667-69
62. Deniges MG: [Analytical chemistry—Study of methyl alcohol in general and especially in the presence of ethyl alcohol.] C R Acad Sci (Paris) 150:832-34, 1910 (Fr)
63. Ellvove E: A note on the detection and estimation of small amounts of methyl alcohol. J Ind Eng Chem 9:295-97, 1917
64. Wright LO: Comparison of sensitivity of various tests for methanol. Ind Eng Chem 19:750-52, 1927
65. Chapin RM: Improved Deniges test for the detection and determination of methanol in the presence of ethyl alcohol. J Ind Eng Chem 13:543-45, 1921
66. Jephcott CM: Determination of methyl alcohol in the air. Analyst 60:588-92, 1935
67. Jansson BO, Larson BT: Analysis of organic compounds in human breath by gas chromatography-mass spectrometry. J Lab Clin Med 74:961-66, 1969
68. Matsumura Y: The adsorption properties of active carbon—II. Preliminary study on adsorption of various organic vapors on active carbon by gas chromatography. Ind Health 3:121-25, 1965
69. Baker RN, Alenty LA, Zack JF Jr: Simultaneous determination of lower alcohols, acetone and acetaldehyde in blood by gas chromatography. J Chromatogr Sci 7:312-14, 1969
70. Hurst RE: A method of collecting and concentrating head space volatiles for gas-chromatographic analysis. Analyst 99:302-05, 1974

71. Occupational Health Hazards in Massachusetts Industries--IV. Wood heel covering, WPA No. 65-14-6060. Boston, Massachusetts Department of Labor and Industries, Division of Occupational Hygiene, 1937
72. Goss AE, Vance GH: Methanol vapors from duplicating machines may be health hazard. Ind Hyg Newsletter 8:15, 1948
73. McAllister RG: Exposure to methanol from spirit duplicating machines. Am Ind Hyg Assoc Q 15:26-28, 1954
74. Dutkiewicz T, Blockowicz A: [Evaluation of exposure to methanol in view of field studies.] Med Pr 18:132-41, 1967 (Pol)
75. Methyl alcohol (methanol), AIHA Hygienic Guide Series. Southfield, Michigan, American Industrial Hygiene Association, 1957
76. Methanol, Data Sheet 407, Revision A. Chicago, National Safety Council, 1967, pp 1-5
77. American Conference of Governmental Industrial Hygienists, Committee on Industrial Ventilation: Industrial Ventilation--A Manual of Recommended Practice, ed 13. Lansing, Michigan, ACGIH, 1974
78. American National Standards Institute: Fundamentals Governing the Design and Operation of Local Exhaust Systems, Z9.2-1971. New York, American National Standards Institute Inc, 1971
79. Bowditch M, Drinker CK, Drinker P, Haggard HH, Hamilton A: Code for safe concentrations of certain common toxic substances used in industry. J Ind Hyg Toxicol 22:251, 1940
80. Cook WA: Maximum allowable concentrations of industrial atmospheric contaminants. Ind Med 14:936-46, 1945
81. Methyl alcohol (methanol), AIHA Hygienic Guide Series. Southfield, Michigan, American Industrial Hygiene Association, 1964
82. American Conference of Governmental Industrial Hygienists, Committee on Threshold Limit Values: Documentation of Threshold Limit Values for Substances in Workroom Air, ed 3. Cincinnati, ACGIH, 1971, pp 155-56
83. American Conference of Governmental Industrial Hygienists: TLVs--Threshold Limit Values for Chemical Substances and Physical Agents in the Workroom Environment with Intended Changes for 1974. Cincinnati, ACGIH, 1974
84. Winell MA: An international comparison of hygienic standards for chemicals in the work environment. Ambio 4:34-36, 1975, p 23

85. Smelyanskiy ZB, Ulanova IP: [New standards for permissible levels of toxic gases, fumes, dust in the air of work areas.] Gig Tru Prof Zabol 5:7-15, 1959 (Rus)
86. Czechoslovakia Committee of MAC (J Teisinger, chmn): Documentation of MAC in Czechoslovakia. Prague, June 1969, pp 114-15
87. Elkins, HB, in Patty FA (ed): Industrial Hygiene and Toxicology, rev ed 2; Toxicology (Fassett DW, Irish DD, eds). New York, Interscience Publishers, 1963, vol 2, pp 1409-22
88. Methyl alcohol (methanol), AIHA Hygienic Guide Series. Southfield, Michigan, American Industrial Hygiene Association, 1964
89. Methanol--Storage and Handling. Wilmington, Delaware, du Pont de Nemours Co, 1974, 10 pp
90. National Electric Code 1975, NFPA No. 70-1975. Boston, Massachusetts, National Fire Protection Association, 1975
91. American National Standards--Occupational and Educational Eye and Face Protection, Z87.1. New York, American National Standards Institute Inc, 1968

VIII. APPENDIX I

METHOD FOR SAMPLING METHYL ALCOHOL IN AIR

General Requirements

- (a) Collect air samples from within the employee's breathing zone.
- (b) Record the following on all sampling data sheets:
 - (1) Date and time of sample collection.
 - (2) Sampling duration.
 - (3) Volumetric flowrate of sampling.
 - (4) Description of sampling location.
 - (5) Serial number of pump.
 - (6) Name of person performing the calibration or sampling.
 - (7) Other pertinent information (temperature, pressure, and information listed in paragraph (i) of Calibration of Equipment).

Recommended Method

The sampling train consists of a silica gel tube and a vacuum pump.

(a) Collect breathing zone samples in a silica gel tube as near as practicable to the employee's face without interfering with his or her freedom of movement. The shirt collar is convenient for this purpose.

(b) Collect the samples with a portable, battery-operated personal sampling pump whose flow can be accurately controlled to within +5% at 0.05 l/min and a silica gel tube.

(c) Operate the sampler at a flowrate of 0.05 l/min or less. Some pumps are designed for high flowrates and some for low; consequently, care

should be taken to use a pump with the proper flowrate, eg, up to 0.20 l/min.

(d) Collect sufficient breathing zone samples to permit calculation of a ceiling exposure for every operation involving exposure to methyl alcohol.

(e) Provide to the analytical laboratory at least one unused silica gel tube from the same batch to correct for the blank.

Air Sampling Equipment

(a) Use silica gel tubes having an inside diameter of 8 mm and two sections of 45/60 or 42/60 mesh silica gel. The adsorbing section should contain 700 mg of silica gel while the backup section should contain 150 mg of silica gel. These two sections must be separated by a 7-mm section plug (one 100-mesh, stainless steel disc between two Teflon cylinder supports), a 12-mm airspace, and another 7-mm section plug.

(b) Use a battery-operated personal sampling pump and a clip for attachment to the employee's clothing. Calibrate all pumps and flowmeters using a calibrated test meter, or other reference as described in the section of this Appendix under Calibration of Equipment.

Calibration of Equipment

Since the accuracy of an analysis can be no greater than the accuracy with which the volume of air is measured, the accurate calibration of a sampling pump is essential to the correct interpretation of the volume indicated. The frequency of calibration is dependent upon the use, care,

and handling to which the pump is subjected. Pumps should also be recalibrated if they have been misused or if they have just been repaired or received from a manufacturer. If the pump receives hard usage, more frequent calibration may be necessary. Regardless of use, maintenance and calibration should be performed on a regular schedule and records of these kept.

Ordinarily, pumps should be calibrated in the laboratory both before they are used in the field and after they have been used to collect a large number of field samples. The accuracy of calibration is dependent on the type of instrument used as a reference. The choice of calibration instrument will depend largely upon where the calibration is to be performed. For laboratory testing, standards such as a spirometer or soapbubble meter are recommended, although other standard calibration instruments, such as a wet test meter, or dry gas meter can be used. The actual setups will be similar for all instruments.

The calibration setup for personal sampling pumps with a silica gel tube is as shown in Figure XIII-1. If another calibration device is selected, equivalent procedures should be used. Since the flowrate given by a pump is dependent on the pressure drop of the sampling device, in this case a silica gel tube, the pump must be calibrated while operating with a representative silica gel tube. Instructions for calibration with the soapbubble meter are as follows:

(a) Check the voltage of the pump battery with a voltmeter to ensure adequate voltage for calibration; charge the battery as needed.

(b) Break the tips of a silica gel tube to produce openings of at least 4-mm in diameter.

- (c) Assemble the sampling train as shown in Figure XIII-1.
- (d) Turn on the pump and moisten the inside of the soapbubble meter by immersing the buret into the soap solution and drawing bubbles up the inside until they travel the entire buret length without bursting.
- (e) Adjust the pump flow controller to the desired flowrate.
- (f) Check the water manometer to ensure that the pressure drop across the sampling train does not exceed 2.0 inches of water at 0.05 l/min.
- (g) Start a soapbubble up the buret and with a stopwatch determine the time it takes the bubble to move from one calibration mark to another.
- (h) Repeat the procedure in (g) at least twice, average the results, and calculate the flowrate by dividing the volume between the preselected marks by the time required for the soapbubble to traverse the distance. If, for the pump being calibrated, the volume of air sampled is the product of the number of strokes times a stroke factor (given in units of volume/stroke), the stroke factor is the quotient of the volume between the two preselected marks divided by the number of strokes.
- (i) Record the following calibration data: volume measured, elapsed time or number of strokes, pressure drop, air temperature, and atmospheric pressure.
- (j) Also record the serial number of the pump, the date, and the name of the person performing the calibration.

Collection of Samples

- (a) Break both ends of the silica gel tube to provide openings of at least half of the internal diameter of the tube, ie, 4 mm. A smaller

opening causes a limiting orifice effect which reduces the flow through the tube. The smaller section of silica gel in the tube is used as a backup section and should therefore be placed nearest the sampling pump. Tubing may be used to connect the back of the tube to the pump, but no tubing must ever be put in front of the silica gel tube. Support the tube in a vertical position for sampling to prevent channeling.

(b) The recommended sampling flowrate is 0.05 l/min or less. A 3-liter sample is normally adequate. Using the manufacturer's directions, set the calibrated flowrate as accurately as possible. Record the temperature, pressure, and humidity of the sampled atmosphere.

(c) Record the initial and final counter readings. The sample volume can be obtained by multiplying the number of counter strokes times the volume/stroke factor.

(d) Immediately after sampling, cap the silica gel tubes with the plastic caps supplied by the manufacturer. Masking tape is the only suitable substitute for sealing the tubes. Rubber caps should never be used.

(e) Treat one silica gel tube in the same manner as the sample tubes (break, seal, ship), but draw no air through it. Label this tube as the blank.

Special Considerations

(a) When two or more compounds are known or suspected to be present in the air, convey such information, including their suspected identities, with the sample.

(b) Because of the high resistance of the silica gel tube, the

sampling pump should not be operated for more than 8 hours without recharging the battery.

(c) With the use of the large size silica gel tubes, the problem of nonquantitative trapping of methyl alcohol in the presence of high humidity or water mist is minimized to a great extent.

(d) Since the desorption efficiency of silica gel varies from batch to batch, all the tubes used to collect a set of samples must contain silica gel from the same batch. Several unused silica gel tubes and information on the batch number should accompany the samples.

Shipping Samples

Capped silica gel tubes should be padded and packed tightly to minimize breakage during transportation. Bulk samples and silica gel tubes must be shipped in separate containers.

IX. APPENDIX II

ANALYTICAL METHOD FOR METHYL ALCOHOL

The following analytical method for methyl alcohol is adapted from that described by Baker et al. [69]

Principle of the Method

(a) A known volume of air is drawn through a silica gel tube; organic vapors are adsorbed on the silica gel. The sample is then desorbed with distilled water.

(b) An aliquot of the aqueous sample is injected directly into a gas chromatograph.

(c) The area under the resulting peak is determined and compared with areas obtained from standards.

Range and Sensitivity

The sampling method is intended to provide a measure of airborne methyl alcohol in the range of 100-1,000 ppm. This method has been validated at methyl alcohol concentrations of 100, 200, and 400 ppm and a sampling time of 60 minutes, and at 1,000 ppm for at least a 15-minute sampling period. [60]

The gas chromatographic method can measure from 1 to 40 $\mu\text{g}/\text{ml}$ of methyl alcohol in aqueous solutions. [69] When used in combination, it is estimated that the sampling and analytic methods will determine as little

as 0.8 ppm methyl alcohol in a 3-liter air sample. For aqueous solutions, the working range for methyl alcohol is linear up to concentrations of 40 $\mu\text{g/ml}$. [69] However, the gas chromatographic method can easily be applied to higher concentrations by appropriate serial dilution of the desorbing solution with distilled water.

Interferences

Any compound which has the same retention time as methyl alcohol at the operating conditions described in this method will interfere with the analysis. The retention time of any substance suspected of being present in the sample should be determined to evaluate the likelihood of its interfering with the procedure.

Precision and Accuracy

The coefficient of variation (Cv) for 10 replicate determinations of methyl alcohol in aqueous samples performed in the same laboratory was 0.025. This value corresponds to a standard deviation of 0.25 $\mu\text{g/ml}$ with a mean of 10.0 $\mu\text{g/ml}$. [69] The efficiency of the combined sampling and analytic method has not yet been established.

Apparatus

- (a) Gas chromatograph equipped with a flame ionization detector.
- (b) Column (183 cm x 5 mm ID) with 60/80 mesh Porapak Q, preconditioned for 18 hours at 225 C.
- (c) A mechanical or electronic integrator or some other method for

determining areas under peaks.

- (d) Glass-stoppered test tubes.
- (e) Microsyringes: 10 μ l and other convenient sizes for making standards and sample injections.
- (f) Volumetric flasks: convenient sizes for making standards.
- (g) Pipets.

Reagents

- (a) Distilled and deionized water.
- (b) Methyl alcohol, chromatographic grade.
- (c) Anhydrous acetonitrile, chromatographic grade.
- (d) Purified nitrogen.
- (e) Purified hydrogen.
- (f) Purified air.
- (g) Industrial grade compressed air (as per instrument requirements).

Procedure

(a) Cleaning of Equipment

All glassware used for laboratory analyses should be washed in detergent followed by tap and distilled water rinses.

(b) Analysis of Samples

(1) Use a suitable aliquot of the aqueous methyl alcohol solution obtained in the sampling procedure (Appendix I). No further preparations of the sample are necessary.

(2) Typical operating conditions for the gas chromatograph are:

(A) 35 ml/min nitrogen carrier gas flow. [69]
(B) Hydrogen gas flow to detector as required by instrument specifications.

(C) Air flowrate to the detector as required by instrument specifications.

(D) 125 C injection port temperature. [69]

(E) 125 C detector temperature. [69]

(F) 100 C isothermal column temperature. [69]

(3) To eliminate difficulties arising from blowback or distillation within the needle, the solvent flush injection technique is used. A 10- μ l syringe is first flushed with solvent several times to wet the barrel and plunger. Three microliters of solvent are drawn into the syringe to increase the accuracy and reproducibility of the injected sample volume. The needle is removed from the solvent, and the plunger is pulled back about 0.2 μ l to separate the solvent from the sample by a pocket of air. The needle is then immersed in the sample and an aliquot (2-7 μ l) is withdrawn. After the needle is removed from the sample and prior to injection, the plunger is pulled back 1.2 μ l to minimize evaporation of the sample from the tip of the needle. If, for example, a 5- μ l aliquot were used, the sample would measure 5.7-5.8 μ l because of the needle volume. Duplicate injections of each sample and standard should be made at a constant injection volume throughout the procedure.

(4) The area under the sample peak is measured by an electronic integrator or some other suitable form of area measurement, and

the $\mu\text{g}/\text{ml}$ of methyl alcohol are read from a standard curve.

Determination of Desorption Efficiency

The desorption efficiency of a particular compound can vary from one laboratory to another and also from one batch of silica gel to another. Thus, it is necessary to determine at least once the percentage of methyl alcohol recovered in the desorption process. This procedure should be repeated for each new batch of silica gel tubes used.

Silica gel, equivalent to the amount in the first section of the sampling tube (700 mg), is measured into a 5-cm, 4-mm ID glass tube, flame-sealed at one end. This silica gel must be from the same batch as that used in obtaining the samples. The open end is sealed with a plastic cap. A measured amount of pure methyl alcohol is injected directly into the silica gel with a microliter syringe, and the tube is capped with plastic. The amount of methyl alcohol used is usually equivalent to that expected in a 3-liter sample of air at the environmental limit.

At least six tubes are prepared in this manner and allowed to stand overnight or longer; this should assure complete adsorption of the methyl alcohol onto the silica gel. These six tubes are referred to as the samples. A tube referred to as the blank should be treated like the sample tubes except that no methyl alcohol is added to it. The blank and sample tubes are desorbed and analyzed in the same manner described above for unknown air samples.

Two or three standards are prepared by injecting identical volumes of methyl alcohol into 1.0 ml of distilled water with the same syringe used in the preparation of the sample. These are analyzed with the samples. The

desorption efficiency (DE) equals the average weight in mg recovered from the tube divided by the weight in mg added to the tube.

$$DE = \frac{\text{average weight recovered (mg)}}{\text{weight added (mg)}}$$

The desorption efficiency is dependent on the amount of analyte collected on the silica gel. The desorption efficiency versus the weight of analyte found should be plotted.

Standard Curve

Prepare a series of standards in the range of 1-40 $\mu\text{g/ml}$ methyl alcohol in distilled water containing 0.1% acetonitrile as an internal standard. Incorporation of the internal standard will adjust for day-to-day variations and variations during the same day due to changes in instrument sensitivity and column performance.

The internal standard is also added in the same concentration to the unknown samples. Standard curves are established by plotting the concentration of methyl alcohol ($\mu\text{g/ml}$) versus the ratio obtained by comparison of the area under the methyl alcohol peak with that under the internal standard peak. The concentration of methyl alcohol in the unknown sample is then calculated by comparison with the standard curve.

Calculations

(a) The concentration, in $\mu\text{g/ml}$, corresponding to each ratio is read from the standard curves for methyl alcohol.

(b) Corrections for the known desorption efficiency of the sampling method must be made for each unknown sample analyzed.

$$\text{corrected } \mu\text{g/ml} = \frac{\mu\text{g/ml from standard curve}}{\text{desorption efficiency}}$$

Convert $\mu\text{g/ml}$ to mg/ml ($1 \mu\text{g} = 0.001 \text{ mg}$).

(c) The concentration of methyl alcohol in the air sampled can be expressed in mg/cu m or in ppm.

$$\text{mg/cu m} = \frac{\text{corrected concentration (mg/ml)} \times \text{volume of desorbant (ml)}}{\text{air volume sampled (cu m)}}$$

$$\text{ppm} = \frac{\text{mg/cu m} \times 24.45 \times 760 \times (T + 273)}{\text{MW} \times \text{P} \times 298}$$

where:

P = Pressure (mmHg) of air sampled

T = Temperature (C) of air sampled

24.45 = Molar volume (liter/mole) at 25 C and 760 mmHg

MW = Molecular weight (g/mole) of methyl alcohol

760 = Standard pressure (mmHg)

298 = Reference temperature of 25 C in degree, Kelvin

X. APPENDIX III
MATERIAL SAFETY DATA SHEET

The following items of information which are applicable to a specific product or material shall be provided in the appropriate block of the Material Safety Data Sheet (MSDS).

The product designation is inserted in the block in the upper left corner of the first page to facilitate filing and retrieval. Print in upper case letters as large as possible. It should be printed to read upright with the sheet turned sideways. The product designation is that name or code designation which appears on the label, or by which the product is sold or known by employees. The relative numerical hazard ratings and key statements are those determined by the rules in Chapter V, Part B, of the NIOSH publication, An Identification System for Occupationally Hazardous Materials. The company identification may be printed in the upper right corner if desired.

(a) Section I. Product Identification

The manufacturer's name, address, and regular and emergency telephone numbers (including area code) are inserted in the appropriate blocks of Section I. The company listed should be a source of detailed backup information on the hazards of the material(s) covered by the MSDS. The listing of suppliers or wholesale distributors is discouraged. The trade name should be the product designation or common name associated with the material. The synonyms are those commonly used for the product, especially formal chemical nomenclature. Every known chemical designation or

competitor's trade name need not be listed.

(b) Section II. Hazardous Ingredients

The "materials" listed in Section II shall be those substances which are part of the hazardous product covered by the MSDS and individually meet any of the criteria defining a hazardous material. Thus, one component of a multicomponent product might be listed because of its toxicity, another component because of its flammability, while a third component could be included both for its toxicity and its reactivity. Note that a MSDS for a single component product must have the name of the material repeated in this section to avoid giving the impression that there are no hazardous ingredients.

Chemical substances should be listed according to their complete name derived from a recognized system of nomenclature. Where possible, avoid using common names and general class names such as "aromatic amine," "safety solvent," or "aliphatic hydrocarbon" when the specific name is known.

The "%" may be the approximate percentage by weight or volume (indicate basis) which each hazardous ingredient of the mixture bears to the whole mixture. This may be indicated as a range or maximum amount, ie, "10-40% vol" or "10% max wt" to avoid disclosure of trade secrets.

Toxic hazard data shall be stated in terms of concentration, mode of exposure or test, and animal used, ie, "6.8 ml/kg LD50-oral-rat," "16.4 ml/kg LD50-skin-rabbit," or "permissible exposure from 29 CFR 1910.93," or, if not available, from other sources of publications such as the American Conference of Governmental Industrial Hygienists or the American National Standards Institute Inc. Flammable or reactive data could be flash point,

shock sensitivity, or other brief data indicating nature of the hazard.

(c) Section III. Physical Data

The data in Section III should be for the total mixture and should include the boiling point and melting point in degrees Fahrenheit (Celsius in parentheses); vapor pressure, in conventional millimeters of mercury (mmHg); vapor density of gas or vapor (air = 1); solubility in water, in parts/hundred parts of water by weight; specific gravity (water = 1); percent volatiles (indicated if by weight or volume) at 70 degrees Fahrenheit (21.1 degrees Celsius); evaporation rate for liquids or sublimable solids, relative to butyl acetate; and appearance and odor. These data are useful for the control of toxic substances. Boiling point, vapor density, percent volatiles, vapor pressure, and evaporation are useful for designing proper ventilation equipment. This information is also useful for design and deployment of adequate fire and spill containment equipment. The appearance and odor may facilitate identification of substances stored in improperly marked containers, or when spilled.

(d) Section IV. Fire and Explosion Data

Section IV should contain complete fire and explosion data for the product, including flash point and autoignition temperature in degrees Fahrenheit (Celsius in parentheses); flammable limits, in percent by volume in air; suitable extinguishing media or materials; special firefighting procedures; and unusual fire and explosion hazard information. If the product presents no fire hazard, insert "NO FIRE HAZARD" on the line labeled "Extinguishing Media."

(e) Section V. Health Hazard Information

The "Health Hazard Data" should be a combined estimate of the hazard of the total product. This can be expressed as a TWA concentration, as a permissible exposure, or by some other indication of an acceptable standard. Other data are acceptable, such as lowest LD50 if multiple components are involved.

Under "Routes of Exposure," comments in each category should reflect the potential hazard from absorption by the route in question. Comments should indicate the severity of the effect and the basis for the statement if possible. The basis might be animal studies, analogy with similar products, or human experiences. Comments such as "yes" or "possible" are not helpful. Typical comments might be:

Skin Contact--single short contact, no adverse effects likely; prolonged or repeated contact, possibly mild irritation.

Eye Contact--some pain and mild transient irritation; no corneal scarring.

"Emergency and First Aid Procedures" should be written in lay language and should primarily represent first aid treatment that could be provided by paramedical personnel or individuals trained in first aid.

Information in the "Notes to Physician" section should include any special medical information which would be of assistance to an attending physician including required or recommended preplacement and periodic medical examinations, diagnostic procedures, and medical management of overexposed employees.

(f) Section VI. Reactivity Data

The comments in Section VI relate to safe storage and handling of hazardous, unstable substances. It is particularly important to highlight instability or incompatibility to common substances or circumstances, such as water, direct sunlight, steel or copper piping, acids, alkalies, etc. "Hazardous Decomposition Products" shall include those products released under fire conditions. It must also include dangerous products produced by aging, such as peroxides in the case of some ethers. Where applicable, shelf life should also be indicated.

(g) Section VII. Spill or Leak Procedures

Detailed procedures for cleanup and disposal should be listed with emphasis on precautions to be taken to protect employees assigned to cleanup detail. Specific neutralizing chemicals or procedures should be described in detail. Disposal methods should be explicit including proper labeling of containers holding residues and ultimate disposal methods such as "sanitary landfill," or "incineration." Warnings such as "comply with local, state, and federal antipollution ordinances" are proper but not sufficient. Specific procedures shall be identified.

(h) Section VIII. Special Protection Information

Section VIII requires specific information. Statements such as "Yes," "No," or "If necessary" are not informative. Ventilation requirements should be specific as to type and preferred methods. Respirators shall be specified as to type and NIOSH or US Bureau of Mines approval class, ie, "Supplied air," "Organic vapor canister," etc. Protective equipment must be specified as to type and materials of construction.

(i) Section IX. Special Precautions

"Precautionary Statements" shall consist of the label statements selected for use on the container or placard. Additional information on any aspect of safety or health not covered in other sections should be inserted in Section IX. The lower block can contain references to published guides or in-house procedures for handling and storage. Department of Transportation markings and classifications and other freight, handling, or storage requirements and environmental controls can be noted.

(j) Signature and Filing

Finally, the name and address of the responsible person who completed the MSDS and the date of completion are entered. This will facilitate correction of errors and identify a source of additional information.

The MSDS shall be filed in a location readily accessible to employees exposed to methyl alcohol. The MSDS can be used as a training aid and basis for discussion during safety meetings and training of new employees. It should assist management by directing attention to the need for specific control engineering, work practices, and protective measures to ensure safe handling and use of the material. It will aid the safety and health staff in planning a safe and healthful work environment and in suggesting appropriate emergency procedures and sources of help in the event of harmful exposure of employees.

MATERIAL SAFETY DATA SHEET

I PRODUCT IDENTIFICATION		
MANUFACTURER'S NAME	REGULAR TELEPHONE NO. EMERGENCY TELEPHONE NO.	
ADDRESS		
TRADE NAME		
SYNONYMS		
II HAZARDOUS INGREDIENTS		
MATERIAL OR COMPONENT	%	HAZARD DATA
III PHYSICAL DATA		
BOILING POINT, 760 MM HG		MELTING POINT
SPECIFIC GRAVITY (H ₂ O = 1)		VAPOR PRESSURE
VAPOR DENSITY (AIR = 1)		SOLUBILITY IN H ₂ O, % BY WT
% VOLATILES BY VOL		EVAPORATION RATE (BUTYL ACETATE = 1)
APPEARANCE AND ODOR		

IV FIRE AND EXPLOSION DATA				
FLASH POINT (TEST METHOD)			AUTOIGNITION TEMPERATURE	
FLAMMABLE LIMITS IN AIR, % BY VOL.	LOWER		UPPER	
EXTINGUISHING MEDIA				
SPECIAL FIRE FIGHTING PROCEDURES				
UNUSUAL FIRE AND EXPLOSION HAZARD				
V HEALTH HAZARD INFORMATION				
HEALTH HAZARD DATA				
ROUTES OF EXPOSURE				
INHALATION				
SKIN CONTACT				
SKIN ABSORPTION				
EYE CONTACT				
INGESTION				
EFFECTS OF OVEREXPOSURE				
ACUTE OVEREXPOSURE				
CHRONIC OVEREXPOSURE				
EMERGENCY AND FIRST AID PROCEDURES				
EYES				
SKIN				
INHALATION				
INGESTION				
NOTES TO PHYSICIAN				

VI REACTIVITY DATA	
CONDITIONS CONTRIBUTING TO INSTABILITY	
INCOMPATIBILITY	
HAZARDOUS DECOMPOSITION PRODUCTS	
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION	
VII SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED	
NEUTRALIZING CHEMICALS	
WASTE DISPOSAL METHOD	
VIII SPECIAL PROTECTION INFORMATION	
VENTILATION REQUIREMENTS	
SPECIFIC PERSONAL PROTECTIVE EQUIPMENT	
RESPIRATORY (SPECIFY IN DETAIL)	
EYE	
GLOVES	
OTHER CLOTHING AND EQUIPMENT	

IX SPECIAL PRECAUTIONS

PRECAUTIONARY
STATEMENTS

OTHER HANDLING AND
STORAGE REQUIREMENTS

PREPARED BY _____

ADDRESS _____

DATE _____

XI. APPENDIX IV
COMBUSTIBLE GAS METER

Combustible gas meters are direct reading instruments and are ordinarily calibrated to read the percentage of the lower explosive limit of a flammable gas or vapor in the air being tested.

Calibration curves must be prepared using the instructions provided by the manufacturer.

The combustible gas meter can be tested by placing a sample of gas from commercially available cylinders in a rubber bellows or internal air pump which is connected to the meter. If the proper reading is not obtained, the instrument should be checked for burnt-out filaments or leaks. This should be repeated with other gases.

XII. APPENDIX V

FUTURE RESEARCH PRIORITIES FOR METHYL ALCOHOL

One of the most pressing research needs for methyl alcohol is the acquisition of updated information concerned with worker exposures and corresponding health effects, if any, in the contemporary workplace environment. The presently available information pertaining to these exposures is seriously inadequate. Most of the data deal either with overexposure to unknown high concentrations and resultant acute effects, or with longer-term exposures without evidence of adverse health effects.

Additionally, much of this information deals with outdated processes. The need to characterize contemporary airborne concentrations of methyl alcohol in industry is amplified by the possibility of stepped-up production and consumption of methyl alcohol if, for example, it were to become a major automotive fuel or fuel additive, for then the number of potentially exposed workers will correspondingly increase. Parallel studies in employees exposed at these concentrations will then need to be pursued. Particular attention should be focused upon the eyes -- specifically the retina, optic disk, and visual function -- and upon the central nervous system. Aided by such modern and sensitive techniques as electroretinography (retinal photography) with the fundus camera and direct ophthalmoscopy as well as electroencephalography to study changes in central nervous system function, the recommended research would serve both immediate and predictive purposes. In such studies, care should be taken to minimize percutaneous absorption of liquid methyl alcohol, so that any

demonstrable effects will be directly related to inhalation of a known airborne methyl alcohol concentration.

Further studies of methyl alcohol toxicity should be undertaken in primates, since their metabolic pathways and clinical signs appear to be somewhat similar to those in humans. There is evidence that the ocular and neurotoxic effects of methyl alcohol in humans are largely mediated by metabolic oxidation products, possibly formaldehyde or formate. Controlled exposures of primates in the laboratory at various concentrations of methyl alcohol vapor, including long-term, low-level intermittent exposures (8-10 hours/day), accompanied by appropriate physiologic, biochemical, macro- and microscopic post-mortem examinations, could yield data on changes hitherto undetected in humans to supplement the epidemiologic studies already proposed. Appropriate caution in quantitatively extrapolating effects in other species, even subhuman primates, to humans should be applied. Studies on primates given formaldehyde or formate in doses corresponding to the experimental methyl alcohol exposures, assuming a stoichiometric conversion to these oxidation products, should be attempted. The occurrence of similar ocular and neurotoxic effects would be supportive evidence that these effects of methyl alcohol in humans are so mediated.

The sampling procedure recommended in this document, while usable, has not been tested in conjunction with the recommended analytic method. NIOSH is currently testing a modified gas chromatographic method (similar to that in this document) to be used in conjunction with the recommended sampling method.

In view of the demonstrated differences in metabolism of methyl alcohol between primates and lower animals, the utility of mutagenic,

teratogenic, or carcinogenic studies in rodents, often the species of choice for such studies, is not clear. Perhaps experimental exposures of rodents to the human metabolites of methyl alcohol would give useful information on these points.

XIII. TABLES AND FIGURE

TABLE XIII-1

PHYSICAL AND CHEMICAL PROPERTIES OF METHYL ALCOHOL

Molecular formula	CH ₃ OH
Formula weight	32.04
Apparent specific gravity at 20 C	0.7910
Boiling point at 760 mmHg	64.5 C
Vapor pressure at 20 C	96 mmHg
Melting point	-97.6 C
Solubility in water	Miscible
Solubility in alcohols, ketones, esters, and halogenated hydrocarbons	Miscible
Flash point, Tag open cup	16 C
Flash point, Tag closed cup	12 C
Flammable limits (% in air)	6.72-36.50
Vapor density (air=1)	1.11
Corrosivity	Noncorrosive at normal atmospheric temperatures. Exceptions: lead and aluminum
Conversion factors (760 mmHg and 25 C)	1 ppm=1.310 mg/cu m 1 mg/cu m=.763 ppm

Adapted from ANSI Z37 [2], the Manufacturing Chemists Association [3],
and the Handbook of Chemistry and Physics [4]

TABLE XIII-2

US METHYL ALCOHOL CONSUMPTION, 1973

	Million Pounds	Million Gallons
Formaldehyde	2,778	420
Dimethyl terephthalate	435	66
Solvent usage	565	85
Methyl halides	435	66
Methylamines	232	35
Methyl methacrylate	265	40
Inhibitor for formaldehyde	66	10
Exports	824	124
Glycol methyl ethers	81	12
Acetic acid	240	36
Miscellaneous	<u>1,207</u>	<u>181</u>
Total	7,128	1,075

From Blackford [5]

TABLE XIII-3

POTENTIAL OCCUPATIONAL EXPOSURES TO METHYL ALCOHOL

Acetic acid makers	Methyl alcohol workers
Adhesive workers	Methyl amine makers
Alcohol distillery workers	Methylation workers
Alcohol lamp users	Methyl bromide makers
Aldehyde pumpmen	Methyl chloride makers
Antifreeze workers	Methyl methacrylate makers
Art glass workers	Millinery workers
Automobile painters	Motor fuel blenders
Aviation fuel handlers	Organic chemical synthesizers
Bookbinders	Painters
Bronzers	Paintmakers
Brushmakers	Paint remover workers
Denatured alcohol workers	Patent leather makers
Dimethyl sulfate makers	Perfume makers
Drug makers	Photoengravers
Drycleaners	Photographic film makers
Dye makers	Polish makers
Dyers	Printers
Ester makers	Rayon makers
Explosives workers	Resin makers
Feather workers	Rocket fuel handlers
Felt-hat makers	Rocket fuel makers
Flower makers, artificial	Rubber shoe cementers
Formaldehyde makers	Rubber workers
Foundry workers	Shellackers
Furniture polishers	Shellac makers
Gilders	Shoe factory workers
Glassmakers, safety	Shoe finishers
Hectograph operators	Shoe heel coverers, wood
Incandescent lamp makers	Shoe stitchers
Inkmakers	Soapmakers
Japan makers	Straw-hat makers
Japanners	Sugar refiners
Jet fuel workers	Textile printers
Lacquerers	Type cleaners
Lacquer makers	Vacuum tube makers
Lasters	Varnish workers
Leather workers	Vulcanizers
Linoleum makers	Wood alcohol distillers
Lithographers	Wood stainers
Metal polishers	Wood stain makers
Methyl acrylate makers	

From Gafafer [6]

TABLE XIII-4

ANIMAL EXPERIMENTATION RESULTS
OF METHYL ALCOHOL EXPOSURE

Species	Route of Exposure	Dose	Effect	Reference
Monkeys	Inhalation	5,000 ppm duration unknown	The monkey survived for an unstated period of time.	47
"	"	1,000 ppm duration unknown	The monkey died promptly upon exposure at this level.	47
Dogs	"	450-500 ppm 8 hr/day 7 days/week for 379 days	Blood levels of methyl alcohol were found to range from 10 to 15 mg/100 ml of blood and on occasion went as high as 52 mg/100 ml. No abnormal eye findings were reported.	41
"	Oral	2.5 to 9.0 g/kg body weight	Of the 9 treated dogs, 2 died at doses of 4 and 9 g/kg. CO ₂ combining capacities dropped below normal in 2 dogs, and no ophthalmoscopic changes were noted.	42

TABLE XIII-4 (CONTINUED)
 ANIMAL EXPERIMENTATION RESULTS
 OF METHYL ALCOHOL EXPOSURE

Species	Route of Exposure	Dose	Effect	Reference
Monkeys	Oral	1.0 to 8.0 g/kg	Acidosis developed in monkeys receiving doses ranging from 3.0 to 6.0 g/kg. The animal receiving 1.0 g/kg did not develop acidosis. Definite eye-ground change occurred to 2 of the acidotic monkeys.	42
Rats	"	4.75 g/kg	70% mortality	42
"	"	4.5 g/kg	None of the 9 tested rats developed acidosis.	42
Rabbits	"	3.5 g/kg	One animal receiving this dose died in less than 24 hours. No eye fundus changes were reported.	42
Rabbits	"	2.1 g/kg	Of the 3 animals tested at this dose, all died between 24 hours and 3 days after dosing.	42
"	Intra-cutaneous	10 mg and 35 mg	At 10 mg, there was no skin reaction, whereas at 35 mg, a 9-sq mm skin reaction occurred.	49

TABLE XIII-4 (CONTINUED)
ANIMAL EXPERIMENTATION RESULTS
OF METHYL ALCOHOL EXPOSURE

Species	Route of Exposure	Dose	Effect	Reference
Monkeys	i.p. inj	0.5 g/kg of 14 C-methyl alcohol with an equimolar amount of ethyl alcohol	The ethyl alcohol reduced the oxidation of methyl alcohol 90%.	52
"	"	1.0 g/kg 14 C-methyl alcohol and 6.0 g/kg 14C-methyl alcohol	The methyl alcohol was oxidized at a rate of 37 mg/kg/hour between the first and fourth hour. The CO ₂ formation was linear at the high dose; the oxidation rate was 47 mg/kg/hour which is a significant difference.	52
Rats	"	1.0/kg 14C-methyl alcohol	The oxidation rate of the methyl alcohol was 24 mg/kg/hr for the first 28 hours. At the end of 36 hours 77% of the methyl alcohol had been oxidized to 14C-labeled CO ₂ and 24% was excreted unchanged in approximately equal amounts by the pulmonary and combined urinary and fecal routes.	51

TABLE XIII-4 (CONTINUED)

ANIMAL EXPERIMENTATION RESULTS
OF METHYL ALCOHOL EXPOSURE

Species	Route of Exposure	Dose	Effect	Reference
Monkeys	i.p. inj	2-4 g/kg.	Consistent development of acidosis. At 4 g/kg methyl alcohol the following occurred: blood bicarbonate (p CO ₂ and total CO ₂) decreased, blood pH decreased, blood pH decreased over 7 1/2 to 21 hours, <u>glucose increased moderately</u> . There was a marked <u>formate</u> increase, also increases of lactate, alpha-hydroxybutyrate, beta-hydroxybutyrate, alpha-ketobutyrate, acetoacetate, p-hydroxyphenylacetate and p-hydroxyphenyllactate.	53

FIGURE XIII-1 CALIBRATION SET UP FOR PERSONAL SAMPLING WITH SILICA GEL TUBE

